Field TOOL New Items

Annular Cutters

Unibor Annular Cutters, Made in England

Annular cutters are very efficient at cutting a hole through steel. They remove only a narrow wall of material, leaving behind a slug which is ejected at the end of the cut. When compared to a twist drill, annular cutters use far less energy and time to do the same work.

Unibor M35 Cobalt cutters offer up to 30% longer life when compared with standard high speed steel. Cobalt cutters feature a heavier wall thickness of 0.265".

Unibor cutters are fully ground and resharpenable.

Cutters from 3/4" to 1-7/16" diameter are typically supplied with a 3/4" Weldon shank.

	HIGH SPEED STEEL				M35 – 5% COBALT					
	1" LENGTH		2" LENGTH		1" LENGTH		2" LENGTH		3" LENGTH	
SIZE	ORDER NO.	PRICE EACH	ORDER NO.	PRICE EACH	ORDER NO.	PRICE EACH	ORDER NO.	PRICE EACH	ORDER NO.	PRICE EACH
7/16	2855-114	$ 18.30	2855-214	$ 27.80	2855-314	$ 23.50	2855-414	$ 32.60	–	–
1/2	2855-116	18.30	2855-216	27.80	2855-316	23.50	2855-416	32.60	–	–
9/16	2855-118	19.50	2855-218	27.80	2855-318	25.60	2855-418	36.10	–	–
5/8	2855-120	21.90	2855-220	30.10	2855-320	28.80	2855-420	38.60	–	–
11/16	2855-122	22.40	2855-222	33.30	2855-322	29.40	2855-422	43.60	–	–
3/4	2855-124	24.20	2855-224	35.80	2855-324	31.70	2855-424	47.00	2855-524	$ 77.30
13/16	2855-126	25.60	2855-226	38.30	2855-326	33.60	2855-426	50.40	2855-526	83.90
7/8	2855-128	27.50	2855-228	41.00	2855-328	36.10	2855-428	53.80	2855-528	89.00
15/16	2855-130	30.00	2855-230	44.50	2855-330	39.40	2855-430	58.40	2855-530	95.30
1	2855-132	32.00	2855-232	48.00	2855-332	42.00	2855-432	63.00	2855-532	105.00
1-1/16	2855-134	32.80	2855-234	49.90	2855-334	43.00	2855-434	65.40	2855-534	113.50
1-1/8	2855-136	37.80	2855-236	57.00	2855-336	49.60	2855-436	74.80	2855-536	124.60
1-3/16	2855-138	39.60	2855-238	58.90	2855-338	52.00	2855-438	77.30	2855-538	127.00
1-1/4	2855-140	42.80	2855-240	61.40	2855-340	53.80	2855-440	80.60	2855-540	134.40
1-5/16	2855-142	44.70	2855-242	63.70	2855-342	56.70	2855-442	83.60	2855-542	136.50
1-3/8	2855-144	55.60	2855-244	68.80	2855-344	72.70	2855-444	89.00	2855-544	138.50
1-7/16	2855-146	62.60	2855-246	76.20	2855-346	82.20	2855-446	100.00	2855-546	146.20
1-1/2	2855-148	65.30	2855-248	81.90	2855-348	85.70	2855-448	107.50	2855-548	155.30
1-9/16	2855-150	73.60	2855-250	91.50	2855-350	96.60	2855-450	120.10	2855-550	173.40
1-5/8	2855-152	76.20	2855-252	98.60	2855-352	100.00	2855-452	129.40	2855-552	186.80
1-11/16	2855-154	80.60	2855-254	101.80	2855-354	105.80	2855-454	133.60	2855-554	192.90
1-3/4	2855-156	85.80	2855-256	108.20	2855-356	112.60	2855-456	142.00	2855-556	205.00
1-13/16	2855-158	89.00	2855-258	112.60	2855-358	116.80	2855-458	147.80	2855-558	213.50
1-7/8	2855-160	93.40	2855-260	121.00	2855-360	122.60	2855-460	158.80	2855-560	229.30
1-15/16	2855-162	99.80	2855-262	127.40	2855-362	131.00	2855-462	167.20	2855-562	241.40
2	2855-164	102.10	2855-264	133.80	2855-364	134.00	2855-464	175.60	2855-564	253.50
2-1/16	–	–	–	–	2855-366	186.40	2855-466	209.00	2855-566	263.30
2-1/8	–	–	–	–	2855-368	199.20	2855-468	217.20	2855-568	274.80
2-3/16	–	–	–	–	2855-370	205.50	2855-470	229.70	2855-570	279.90
2-1/4	–	–	–	–	2855-372	207.10	2855-472	235.80	2855-572	287.40
2-5/16	–	–	–	–	2855-374	213.70	2855-474	239.40	2855-574	293.90
2-3/8	–	–	–	–	2855-376	218.30	2855-476	242.80	2855-576	299.50
2-7/16	–	–	–	–	2855-378	223.00	2855-478	252.30	2855-578	307.90
2-1/2	–	–	–	–	2855-380	228.60	2855-480	264.10	2855-580	315.40
2-9/16	–	–	–	–	2855-382	233.30	2855-482	280.40	2855-582	328.40
2-5/8	–	–	–	–	2855-384	252.00	2855-484	285.90	2855-584	335.90
2-11/16	–	–	–	–	2855-386	254.60	2855-486	291.70	2855-586	342.40
2-3/4	–	–	–	–	2855-388	268.70	2855-488	297.60	2855-588	349.90
2-13/16	–	–	–	–	2855-390	283.20	2855-490	326.60	2855-590	353.60
2-7/8	–	–	–	–	2855-392	286.10	2855-492	331.70	2855-592	361.10
2-15/16	–	–	–	–	2855-394	290.30	2855-494	342.60	2855-594	367.60
3	–	–	–	–	2855-396	293.20	2855-496	346.80	2855-596	372.30

Model EQ35N

Portable Magnetic Drill

- High-Torque motor
- Safety interlocked controls
- Supplied coolant system
- Lightweight
- QuickHitch arbor
- Includes: Warranty, Carrying case, Allen keys, Safety strap & guard, Cutting oil

- POWER: 1.5 hp
- ELECTRIC MOTOR: 1100 watts, 120V, 10 amps
- SPEED: (no load) 450 rpm
- HEIGHT: 14" • WEIGHT: 25 lbs.
- MAGNETIC DIMENSIONS: 6-1/4" x 3-1/8" x 2"
- MAGNETIC ADHESION: 1300 lbs.
- STROKE: 4-3/4" • CUTTING THICKNESS: 1/2"- 2"

Order No. 2854-800 Price Each: $ 821.40

Model EQ50

Portable Magnetic Drill

- Integral arbor support
- Solid state electronic control panel
- Supplied coolant system
- Quick conversion to twist drilling
- Available with reverse

- POWER: 1.5 hp
- ELECTRIC MOTOR: 1100 watts, 110V, 9 amps
- SPEED: (no load) 280/500 rpm
- HEIGHT: 15-1/2" • WEIGHT: 40 lbs.
- MAGNETIC DIMENSIONS: 7-3/8" x 4" x 2-3/8"
- MAGNETIC ADHESION: 2000 lbs.
- STROKE: 6-5/8" • MORSE TAPER: 2
- CUTTING THICKNESS: 1/2"- 2"

Order No. 2854-005 Price Each: $ 1339.30

Model EQ100

Portable Magnetic Drill

- Integral arbor support
- Solid state electronic control panel
- Supplied coolant system
- Variable speed control
- Quick conversion to twist drilling
- Two gear ranges • Available swivel base
- 4" broaching capacity • QuickHitch arbor
- Available with reverse

- POWER: 2.4 hp
- ELECTRIC MOTOR: 1800 watts, 110V, 10.6 amps
- SPEED: (no load) 40-130 rpm, 145-430 rpm
- HEIGHT: 21" • WEIGHT: 58 lbs.
- MAGNETIC DIMENSIONS: 7-1/2" x 4" x 2-1/2"
- MAGNETIC ADHESION: 4000 lbs.
- STROKE: 4-3/4" • MORSE TAPER: 3
- CUTTING THICKNESS: 1/2"- 3"

Order No. 2854-810 Price Each: $1517.90

Field TOOL SALES: 800-993-4353 Order Online: www.fieldtool.com
FAX: 800-221-3519 Email: sales@fieldtool.com

All prices and discounts subject to change without written notice. Any typographic error is subject to correction. © Field Tool Supply Company 2009