

# AIR & POWER TOOLS

Blow Gun . . . . .	414, 428-431
Compressor Accessories . . . . .	427
Couplers . . . . .	419-422
Cross-Reference Chart . . . . .	417-418
Die Grinders . . . . .	412
Drills . . . . .	413
Dryer, Air Line . . . . .	432
Filters . . . . .	424
Grinders . . . . .	414
Hose & Tubing . . . . .	416, 434
Hose Ends . . . . .	433

In-Line FRL's . . . . .	433
Lubricators . . . . .	425-426
Nylon Tube Fittings . . . . .	416
Plugs . . . . .	419-422
Regulators . . . . .	425-426
Sanders . . . . .	414-415
Saw, Cut-Off . . . . .	413
Scalers . . . . .	414
Signal Bells . . . . .	434
Swivels . . . . .	433
Tank Valves . . . . .	434
Tire Gages . . . . .	431-432
Wrenches . . . . .	415

## POWER TOOLS

Rotary Tools . . . . .	435
Engraver . . . . .	435
Accessories . . . . .	435-436



## 1/4" Air Die Grinder



**1-YEAR  
Warranty**

- All ball bearing construction • Self locking safety throttle to prevent accidental starts
- Ergonomic positive grip • Rear exhaust • Viking Model # VT3000, VT3005

ORDER NO.	AIR SPEED (R.P.M.)	AIR COLLECT SIZE	AIR PRESSURE (P.S.I.)	AIR CONSUMPTION (CFM)	PRICE EACH
3280-700	25,000	1/4"	90	14	\$43.00

## 1/4" Extended Die Grinder



**1-YEAR  
Warranty**

- Durable precision machined and hardened steel gears
- Precision air motor with exceptionally high turning force
- Ergonomic square handle design for positive grip • High quality ball bearings for longer tool life
- Safety throttle lever • Rear exhaust • Industrial duty • Model VT3002E

ORDER NO.	AIR SPEED (R.P.M.)	AIR COLLECT SIZE	AIR PRESSURE (P.S.I.)	AIR CONSUMPTION (CFM)	PRICE EACH
3280-706	22,000	1/4"	90	4	\$125.00

## 1/4" Mini Angle Die Grinder



**1-YEAR  
Warranty**

- Lightweight and versatile design
- Great for hard-to-reach areas
- Features 20,000 RPM reliability, minimal vibration
- Model VT3000A

ORDER NO.	AIR SPEED (R.P.M.)	AIR COLLECT SIZE	AIR PRESSURE (P.S.I.)	AIR CONSUMPTION (CFM)	PRICE EACH
3280-704	20,000	1/4"	100	4	\$96.00

## 1/2" Heavy Duty Reversible Drill

- One hand quick reverse lever
- Ergonomic design, elastomer handle grip
- Heavy duty ball and needle bearing construction
- Planetary gear reduction balances the drilling load, maximizing performance
- Precision air motor with exceptionally high turning force • Model VT5007



ORDER NO.	AIR SPEED (R.P.M.)	CHUCK SIZE	SPINDLE THREAD	AIR CONSUMPTION (CFM)	PRICE EACH
3280-713	800	1/2"	3/8"-24	4	\$191.00

## 1/2" Non-Reversing Heavy Duty Drill

- Compact, low profile angle head enables easy access to tight areas
- Light weight and powerful
- Comfortable lever throttle
- One hand quick reverse lever
- Ergonomic design with elastomer handle grip for improved comfort
- Heavy duty ball and needle bearing construction
- Planetary gear reduction balances the drilling load and maximizes performance
- Precision air motor with exceptionally high turning force • Model No. V5006



ORDER NO.	AIR SPEED (R.P.M.)	CHUCK SIZE	SPINDLE THREAD	AIR CONSUMPTION (CFM)	PRICE EACH
3280-712	1,500	3/8"	3/8"-24	4	\$223.00

## 4" Angle Grinder

- Precision air motor with exceptionally high turning force
- Sealed ball bearing motor
- Compact body for working in tight places
- Front exhaust keeps working area clear
- Safety locking lever with variable throttle to prevent accidental starts
- Removable side handle for left or right hand operation
- Unique motor controller that virtually eliminates over speeding
- Precision gearing (bevel/pin) for long life/smooth operation
- Uses Type 27 4" capacity wheels • Model No. VT3104



ORDER NO.	AIR SPEED (R.P.M.)	WHEEL SIZE	SPINDLE THREAD	AIR PRESSURE (P.S.I.)	AIR CONSUMPTION (CFM)	PRICE EACH
3280-718	11,000	4"	3/8"-24	90	6	\$226.00

## 4.5"/5" Right Angle Grinder

- Precision air motor with exceptionally high turning force
- Sealed ball bearing motor
- Compact body for working in tight places
- Front exhaust keeps working area clear
- Safety locking lever with variable throttle to prevent accidental start-ups
- Removable side handle for left or right hand operation
- Unique motor controller that virtually eliminates over speeding
- Precision gearing (bevel/pin) for long life and smooth operation
- Includes guard, hex wrenches and spanner
- Uses Type 27 4.5"/5" capacity wheels • Model No. VT3105



ORDER NO.	AIR SPEED (R.P.M.)	CHUCK SIZE	MAX. PRESSURE (PSI)	AIR CONSUMPTION (CFM)	PRICE EACH
3280-719	11,000	1/4"	90-100	6	\$233.00

## Air Needle Scaler, Pistol Grip Handle

- Heat treated barrels and pistons for extended tool life
- Comfortable throttle lever
- Ergonomic rubber grip for greater vibration absorption and operator convenience
- Needles are made from Chrome Vanadium SCM-4 steel heat treated for extended life
- Model No. VT6202



ORDER NO.	BLOWS PER MIN. (B.P.M.)	NEEDLE SIZE	MAX. PRESSURE (PSI)	AIR CONSUMPTION (CFM)	PRICE EACH
3280-752	3,700	0.12"(3mm) 7" long	90	10	\$233.00



## 3/8" Professional Impact Wrench

- Durable pin clutch impact mechanism
- Ergonomic contoured elastomer handle grip for improved comfort
- Built in regulator with 4 power settings
- Easy touch trigger provides greater control and operator comfort
- Model VT2100



ORDER NO.	SQUARE DRIVE	FREE SPEED (R.P.M.)	MAX TORQUE (FT/LBS)	AIR CONSUMPTION (CFM)	PRICE EACH
3280-710	3/8"	10,000	75	3	\$173.00

## 1/2" Professional Impact Wrench

- Durable pin clutch impact mechanism
- Ergonomic contoured elastomer handle grip for improved comfort
- Handle exhaust directs the air away from operator and workpiece
- 360° air inlet swivel prevents air hose from becoming twisted or kinked, for snag-free operator comfort
- Push button forward/reverse for single hand operation
- Easy touch trigger provides greater control and operator comfort
- Model VT2101



ORDER NO.	SQUARE DRIVE	FREE SPEED (R.P.M.)	MAX TORQUE (FT/LBS)	AIR CONSUMPTION (CFM)	PRICE EACH
3280-756	1/2"	8,000	241-400	13.6	\$ 212.00

## 1/2" General Purpose Impact Wrench

- Economical rocking dog impact delivers smooth operation and max. durability
- Built in regulator with 4 power settings
- Delivers max. torque in the reverse direction
- One hand push button forward and reverse
- Model VT2000



ORDER NO.	SQUARE DRIVE	FREE SPEED (R.P.M.)	MAX TORQUE (FT/LBS)	AIR CONSUMPTION (CFM)	PRICE EACH
3280-711	1/2"	7,000	230	16	\$77.00

## 3/8" Ratchet Wrench



- Planetary gear design • Combines speed and power for small applications
- Lever throttle for easy operation and enhanced speed control
- Great for hard-to-reach areas
- Lightweight and well balanced
- Model VT1001

ORDER NO.	SQUARE DRIVE	FREE SPEED (R.P.M.)	MAX TORQUE (FT/LBS)	AIR CONSUMPTION (CFM)	PRICE EACH
3280-725	3/8"	150	45	14	\$66.00

## Mini Saw Cut-Off Tool

- Features a 3" Heavy Duty wheel and metal guard for operator safety
- 20,000 RPM direct drive motor provides low vibration cutting with a safety throttle lever
- Model No. V325



**2-YEAR  
Warranty**

ORDER NO.	AIR SPEED (R.P.M.)	INLET NPT	HOSE SIZE	AIR CONSUMPTION (CFM)	PRICE EACH
3280-749	20,000	1/4	3/8"	4	\$173.00

## 3/8" Belt Sander

- Precision air motor, exceptionally high turning force
- Anti-slip on drive drum
- Used for internal/external finishing
- Quick change belt replacement system
- Lightweight ergonomic handle design for control & comfort
- 360° head rotation is versatile for every job
- Model VT4501



ORDER NO.	AIR SPEED (R.P.M.)	AIR CONSUMPTION (CFM)	BELT SIZE	PRICE EACH
3280-731	16,000	8	3/8 x 13	\$156.00

## Air Blow Gun - 2 Tips

- 1/4" NPT Threads
- 11 CFM - OSHA round tip • 8 CFM - Point tip
- Easy one-hand operation
- Baked dry powder finish for maximum durability
- Model No. VT9000



ORDER NO.	WEIGHT (LBS)	THREAD SIZE - NPT	AIR CONSUMPTION (CFM)	PRICE EACH
3280-722	.035	1/4"	11	\$5.00

# Coupler & Plug Interchanges

With the Milton "Match-up system" all couplers and plugs with same letter code (on face of skin-card) can be used together regardless of thread sizes. Milton "M" style "Kwik-change" couplers and plugs will INTERCHANGE with all manufacturers who comply with the dimensional requirements of military specification MIL-C-4109

MILTON	AMFLO	ARO	CAMEL	COIL HOSE	DIXON	FORNEY	LINCOLN	NAPA	PARKER	TRU-FLATE	MILTON
<b>1/4" Basic size: MILTON INDUSTRIAL "M" STYLE</b>											
711	C20-AU		61-572			75305	5878	90-669		13-201	711
715	C20	MSCF22-000	61-573	150	DC20	75317	632004	90-670	B23	13-235/13-236	715
716	C21	MSCM22-000	61-574	152	DC21	75316		90-672	B22	13-224/13-225	716
717	C20-42	MSCH22-000	61-575	153	DC2042	75480		90-671	B20-3B	13-264	717
717-6	C20-44	MSCH23-000	61-720		DC2044					13-266	717-6
718	C20-23	MSCF23-000	61-718	151	DC2023	75479		90-667	B23E	13-236	718
719	C21-03	MSCM23-000	61-716	155	DC2103			90-657	B22E	13-225	719
726	CP21-01	23902-110		1504	DC2101		630102	90-675	H0C		726
727	CP21	23902-210	61-578	1501	DCP21	75301	630104	90-674	H2C	12-224/12-225	727
728	CP20	23902-200	61-579	1502	DCP20	75302	630204	90-676	H3C	12-234/12-235	728
729	CP20-21	23902-100		1509	DCP2021			90-665	H1C		729
731	CP22		61-023								731
732	CP20-23	23902-300		1505	DCP2023			90-659	H3C-E	12-236	732
733	CP21-03	23902-310	61-535	1503	DCP2103	75471		90-677	H2C-E	12-226	733
736	CP21-42	23902-220	61-576	1506	DCP2142			90-673	H8C	12-264	736
736-6	CP21-44	23902-420		1508	DCP2144	75472			H9C	12-266	736-6
745						75527				13-510/13-511	745
746						75526				13-508/13-509	746
755	C40B	MSCF22-X00	61-013		DCB20	75520		90-615	B33	13-755	755
756	C41B	MSCM22-X00	61-011		DCB21	75521		90-617	B32	13-756	756
1717-4	C20-42L	MSCP22-000							B20-3BP		1717-4
1717-6	C20-44L	MSCP23-000							B20-5BP		1717-6
1736-4	CP21-42L	23902-227							H8CP		1736-4
1736-6	CP21-44L	23902-228							H9CP		1736-6
<b>1/4" Basic size: ARO 210 "A" STYLE</b>											
772						75522				13-301	772
775	C38, C46	210	61-518, 61-526	140	DC38	75318		90-613	B53	13-334/13-335	775
776	C37, C45	210-212	61-527, 61-581		DC37	75482			B50	13-324/13-325	776
776-4	C38-42	210-022			DC3842			90-679	B50-3BP		776-4
776-6	C38-44	210-215			DC3844				B50-5BP		776-6
777	CP37	2608	61-528	1401	DCP37	75303	13329	90-618	A2C	12-324/12-325	777
777-4	CP37-42	3946		1406	DCP3742				A8C		777-4
777-6	CP37-44	22238			DCP3744						777-6
778	CP38	2609	61-529	1402	DCP38	75473	13331	90-620	A3C	12-334/12-335	778
1776-4	C38-42L	210-227									1776-4
1776-6	C38-44L	210-028									1776-6
1777-4	CP37-42L	6944							A8CP		1777-4
1777-6	CP37-44L										1777-6
<b>3/8" Basic size: ARO "AA" STYLE</b>											
1875	C36	310			DC36						1875
1877	CP35	3804			DCP35						1877
1878	CP36	3806			DCP36						1878
<b>1/4" Basic size: LINCOLN "L" STYLE</b>											
790	C28	LNCF22-000	61-548	170	DC28	75523 w/plug	815	90-644	B73	13-434/13-435	790
791	CP27	LNP22-000	61-550	1701	DCP27	75304	11659	90-648	L2C	12-424/12-425	791
792	CP28	LNPF22-000	61-551	1702	DCP28	75524	11661	90-650	L3C	12-434/12-435	792
794	C27	LNCM22-000	61-486		DC27	75525		90-645		13-424/13-425	794
<b>1/4" Basic size: TRU-FLATE/PARKER "T" STYLE</b>											
779	CP12		61-544							12-104	779
780			61-543					90-634			780
781	CP14		61-552					90-652			781
782						75519		90-624		13-101	782
783	CP1	TFPM22-000	61-538	1601	DCP1	75300	5872	90-628	2C	12-124/12-125	783
783-4	CP1-42	TFPH22-000		1606	DCP142	75470		90-630	8C	12-117	783-4
783-6	CP1-44	TFPH23-000		1608	DCP143			90-626	9C		783-6
784	CP2	TFPF22-000	61-539	1602	DCP2	75308	5873	90-600	3C	12-134/12-135	784
785	C2	TFCF22-000	61-523	160	DC2	75315	5871	90-610	B13	13-134/13-135	785
786	C1	TFCM22-000	61-524	162	DC1	75309	5870	90-607	B12	13-124/13-125	786
786-4	C2-42	TFCH22-000		163	DC242			90-611	B10-3B	13-164	786-4
786-6	C2-44	TFCH23-000		166	DC244			90-609	B10-5B		786-6
787	C2R		61-487, 61-545			75478				13-136/13-137	787
788	C2-23	TFCF23-000	61-704							13-138	788
789	C1-03	TFCM23-000			DC103						789
1783-4	CP1-42L	TFPP22-000							8CP		1783-4
1783-6	CP1-44L	TFPP23-000							9CP		1783-6
1786-4	C2-42L	TFCH22-000							B10-3BP		1786-4
1786-6	C2-44L	TFCH23-000							B10-5BP		1786-6

# Universal Couplers



## 5 In ONE™ Universal Safety Exhaust Coupler

The 5 In ONE™ Universal Industrial Safety Exhaust couplers by Milton are designed to safely bleed off air pressure before releasing the connector. The safety exhaust feature allows for safe disconnection, eliminating potentially dangerous hose whip. The coupler remains connected to the plug while pressurized air is safely bled off. Ideal for applications required a durable and long lasting pneumatic coupler, Milton's safety couplers are constructed of heavy-duty steel. Connects to all major interchanges including Industrial (M-style), High flow (V-Style), Automotive (T-Style), Aro (A-Style), and Lincoln (L-Style).



### Specifications:

- Compatible with Industrial (M-style), High flow (V-style), Automotive (T-style), Aro (A-style), and Lincoln (L-Style).
- Available in 1/4" and 3/8" thread size in both Female and Male NPT

- S-1750 - 1/4" Female NPT - Order No. 3351-836 Price Each: \$21.84
- S-1751 - 1/4" Male NPT - Order No. 3351-839 Price Each: \$21.84
- S-1752 - 3/8" Female NPT - Order No. 3351-842 Price Each: \$23.36
- S-1753 - 3/8" Male NPT - Order No. 3351-845 Price Each: \$23.36

## 5 In ONE™ Universal Quick Connect Coupler

Milton's 5 In ONE™ Universal Industrial couplers are designed to Connects to all major interchanges: Industrial (M-style), High flow (v-style), automotive (t-style), Aro (A-style), and Lincoln (L-Style). Constructed of heavy-duty steel which is ideal for applications requiring a durable and long lasting pneumatic coupler.



### Specifications:

- Compatible with Industrial (M-style), High flow (v-style), Automotive (t-style), Aro (A-style), and Lincoln (L-Style)
- 1/4" NPT - Female or Male
- 6 Ball Construction for long life

- S-743 - 1/4" Female NPT  
Order No. 3351-830 Price Each: \$17.12

- S-744 - 1/4" Male NPT  
Order No. 3351-833 Price Each: \$17.12

## Coupler & Plug Interchanges (Continued)

MILTON	AMFLO	ARO	CAMEL	COIL HOSE	DIXON	FORNEY	LINCOLN	NAPA	PARKER	TRU-FLATE	MILTON
<b>3/8" Basic size: MILTON INDUSTRIAL "H" STYLE</b>											
1796-6	C26-44L	MSCP33-000							24-5BP		1796-6
1797-6	CP25-44L	23903-28							H5EP		1797-6
1833	C26-22	MSCM32-000		582	DC2622			90-629	25C		1833
1834	C25-02							90-625			1834
1835	C26	MSCF33-000	61-482	580	DC26	75321	642006	90-680	25	13-536/13-537	1835
1836	C25	MSCM33-000	61-483	581	DC25	75483		90-682	24	13-526/13-527	1836
1836-6	C26-44	MSCH33-000		586	DC2644			90-635	24-6B		1836-6
1837	CP25	23903-310	61-484	5801	DCP25	75307	640108	90-683	H2E	12-526/12-527	1837
1837-6	CP25-44	23903-420		5806	DCP2544			90-651	H5E		1837-6
1838	CP26	23903-300	61-485	5802	DCP26	75474	640206	90-681	H3E	12-536/12-537	1838
1839	CP25-02	23903-210		5803	DCP2502		640104	90-605	H0E	12-525	1839
1840	CP26-22	23903-200		5804	DCP2622		640204	90-606	H1E	12-535	1840
<b>3/8" Basic size: TRU-FLATE/PARKER "P" STYLE</b>											
1746-6	C6-44L	TFCP23-000							14-5BP		1746-6
1747-6	CP5-44L	TFPP23-000							5EP		1747-6
1803	C8	TFCF32-000	61-476	592	DC8	75485		90-686	15C	13-610/13-611	1803
1804	C7	TFCM32-000	61-478		DC7			90-684		13-602	1804
1805	C6	TFCF33-000	61-553	590	DC6	75320	5874	90-654	15	13-612/13-613	1805
1806	C5	TFCM33-000	61-554	591	DC5	75484		90-656	14	13-604	1806
1806-6	C6-44	TFCH33-000		598	DC644			90-521	14-5B	13-666	1806-6
1807	CP5	TFPM33-000	61-558	5901	DCP5		5875	90-658	2E	12-604/12-605	1807
1807-6	CP5-44	TFPH33-000		5906	DCP544			90-530	5E		1807-6
1808	CP6	TFPF33-000	61-559	5902	DCP6	75476	5876	90-660	3E	12-612	1808
1809	CP7	TFPM32-000	61-480	5903	DCP7	75475		90-685	0E	12-602/12-603	1809
1810	CP8	TFPF32-000	61-481	5904	DCP8			90-687	1E	12-610	1810
<b>1/2" Basic size: MILTON INDUSTRIAL "G" STYLE</b>											
1813	C10-23	TFCF43-000	61-472	123	DC1023			90-690	17E	13-710	1813
1814	C9-03	TFCM43-000		121	DC903			90-688	16E	13-702	1814
1815	C10	TFCF44-000	61-563	120	DC10		652008	90-662	B37	13-712/13-713	1815
1816	C9	TFCM44-000	61-564	122	DC9			90-664	B36	13-704	1816
1855											1855
1857	CP17	23904-410	61-134	1201	DCP17		650108	90-578	H2F	12-752	1857
1858	CP18	23904-400	61-137	1202	DCP18		650208	90-588	H3F	12-762	1858
1859	CP17-03	23904-310	61-133	1203	DCP1703		650106	90-575	H0F		1859
1860	CP18-23	23904-3	61-136	1204	DCP1823		650206	90-587	H1F		1860
<b>1/2" Basic size: TRU-FLATE/PARKER "G" STYLE</b>											
1813	C10-23	TFCF43-000	61-472	123	DC1023			90-690	17E	13-710	1813
1814	C9-03	TFCM43-000		121	DC903			90-688	16E	13-702	1814
1815	C10	TFCF44-000	61-563	120	DC10			90-662	B37	13-712/13-713	1815
1816	C9	TFCM44-000	61-564	122	DC9			90-664	B36	13-704	1816
1817	CP9	TFPM44-000	61-568		DCP9			90-666	2F	12-704/12-705	1817
1818	CP10	TFPF44-000	61-569		DCP10			90-668	3F	12-712	1818
1819	CP9-03	TFPM43-000	61-474		DCP903			90-689	0F	12-702	1819
1820	CP10-23	TFPF43-000	61-475		DCP1023			90-691	1F	12-710	1820


No liability is assumed resulting from the use of the information contained herein.




# Air Couplers & Plugs



## Milton Industrial Interchange Series



S-715



S-716



717

Ctn. Qty.: 10

**"M"STYLE 1/4" BASIC SIZE**

NPT THREAD	FEMALE	ORDER NO.	PRICE EACH	MALE	ORDER NO.	PRICE EACH	BARB	ORDER NO.	PRICE EACH
<b>COUPLERS</b>									
1/4"	S-715	3350-389	\$6.76	S-716	3350-392	\$6.76	717	3350-394	\$8.72
3/8"	S-718	3350-399	\$8.76	S-719	3350-402	\$8.76	717-6	3350-396	\$9.25



S 728



S 727



S 736


Ctn. Qty.: 10, Male/Female: 2/cd

**"M"STYLE 1/4" BASIC SIZE**


NPT THREAD	FEMALE	CARD PACK	ORDER NO.	PRICE PER CARD	MALE	CARD PACK	ORDER NO.	PRICE PER CARD	BARB	ORDER NO.	PRICE EACH
<b>PLUGS</b>											
1/4"	S-728	2	3350-409	\$3.24	S-727	2	3350-406	\$3.09	736	3350-419	\$3.50
3/8"	S-732	2	3350-414	\$5.84	S-733	2	3350-417	\$5.66	736-6	3350-421	\$3.55

**"M-STYLE 1/4" COUPLER & PLUG COMBOS AND KITS**

KIT PART NO.	DESCRIPTION	COUPLER	PLUG	CTN. QTY.	ORDER NO.	PRICE EACH
S-711	M style coupler & plug combo	(1) 715	(1) 727	10	3350-383	\$8.24
S-210	M style coupler & plug kit- 12 pc.	(2) 715	(8) 727, (2) 728	5	3350-068	\$28.53
S-211	M style coupler & plug kit- 5 pc.	(1) 715	(3) 727, (1) 728	10	3350-069	\$12.86
S-212	M style coupler & plug kit- 7 pc.	(1) 715	(3) 727, (3) 728	10	3350-070	\$16.07



S-1833



S-1836



S-1836-6

Ctn. Qty.: 5

**"H"STYLE 3/8" BASIC SIZE**

NPT THREAD	FEMALE	ORDER NO.	PRICE PER CARD	MALE	ORDER NO.	PRICE PER CARD	BARB	ORDER NO.	PRICE EACH
<b>COUPLERS</b>									
1/4"	S-1833	3350-995	\$15.10	1834	3350-997	\$14.94	-	-	-
3/8"	S-1835	3351-000	\$15.40	S-1836	3351-003	\$15.40	1836-6	3351-005	\$16.79


**"H"STYLE 3/8" BASIC SIZE**

Ctn. Qty.: 10, Male/Female: 2/cd

NPT THREAD	FEMALE	CARD PACK	ORDER NO.	PRICE PER CARD	MALE	CARD PACK	ORDER NO.	PRICE PER CARD	BARB	ORDER NO.	PRICE EACH
<b>PLUGS</b>											
1/4"	S-1840	2	3351-018	\$5.66	S-1839	2	3351-015	\$5.57	-	-	-
3/8"	S-1838	2	3351-012	\$6.35	S-1837	2	3351-007	\$6.22	1837-6	3351-009	\$4.17



S-1815



S-1816

Ctn. Qty.: 5

**"G"STYLE 1/2" BASIC SIZE**

NPT THREAD	FEMALE	ORDER NO.	PRICE EACH	MALE	ORDER NO.	PRICE EACH
<b>COUPLERS</b>						
3/8"	1813	3350-976	\$18.32	1814	3350-977	\$18.07
1/2"	S-1815	3350-979	\$18.97	S-1816	3350-982	\$18.85
<b>PLUGS</b>						
1/4"	-	-	-	1855	3351-020	\$4.19
3/8"	1860	3351-024	\$4.90	1859	3351-023	\$4.28
1/2"	1858	3351-022	\$5.29	1857	3351-021	\$4.65

## M-Style Couplers & Plugs

Milton M-style "Kwik-change" couplers and plugs will interchange with all manufacturers who comply with the dimensional requirements of military specification MIL-C-4109.

- M-style coupler bodies are brass with brass sleeves
- M-style plugs are case hardened steel, plated to resist rust
- Maximum inlet pressure: 300 PSI
- Maximum temperature: 250° F
- Air flow: 40 SCFM
- Seals: Buna-N

**WARNING: COUPLERS IN THIS SECTION ARE FOR USE WITH SHOP AIR ONLY.**

## M-Style Synthetic Washer

- Replacement M-style part # 768
- Sold in standard packs of 10 only.

**Order No. 3350-457 Price Each: \$0.55**

## H-Style Couplers & Plugs

- H-style coupler bodies steel, plated to resist rust
- H-style plugs are case hardened steel plated to resist rust
- Maximum inlet pressure: 300 PSI
- Maximum temperature: 250° F
- Seals: Buna-N

**WARNING: COUPLERS IN THIS SECTION ARE FOR USE WITH SHOP AIR ONLY.**

## G-Style Couplers & Plugs (Industrial Interchange)

- G-style coupler bodies are steel, plated to resist rust
- G-style plugs are case hardened steel, plated to resist rust
- Maximum inlet pressure: 300 PSI
- Maximum temperature: 250° F
- Air flow: 99 SCFM
- Seals: Buna-N

**WARNING: COUPLERS IN THIS SECTION ARE FOR USE WITH SHOP AIR ONLY.**


# Air Couplers & Plugs



## ARO Interchange Series



S-775



S-776



S-776-4

Ctn. Qty.: 10

### "A 210" STYLE 1/4" BASIC SIZE

NPT THREAD	FEMALE	ORDER NO.	PRICE EACH	MALE	ORDER NO.	PRICE EACH	BARB	ORDER NO.	PRICE EACH
<b>COUPLERS</b>									
1/4"	S-775	3350-460	\$9.09	S-776	3350-463	\$10.14	776-4	3350-465	\$11.97
3/8"	-	-	-	-	-	-	776-6	3350-466	\$12.87

## A 210 Style Couplers & Plugs

- A-style couplers are push type
- A-style coupler bodies are steel, plated to resist rust
- A-style plugs are case hardened steel, plated to resist rust
- Maximum inlet pressure: 300 PSI
- Maximum temperature: 250° F
- Air flow: 34 SCFM
- Seals: Buna-N

**WARNING: COUPLERS IN THIS SECTION ARE FOR USE WITH SHOP AIR ONLY.**



S-777



S-778



S-777-4


Ctn. Qty.: 10 Male/Female: 2/cd

### "A 210" STYLE 1/4" BASIC SIZE


NPT THREAD	FEMALE	CARD PACK	ORDER NO.	PRICE PER CARD	MALE	CARD PACK	ORDER NO.	PRICE PER CARD	BARB	ORDER NO.	PRICE EACH
<b>PLUGS</b>											
1/4"	S-778	2	3350-475	\$3.47	S-777	2	3350-468	\$3.26	777-4	3350-470	\$3.27
3/8"	-	-	-	-	-	-	-	-	777-6	3350-472	\$4.31

### A-STYLE 1/4" COUPLER & PLUG COMBOS AND KITS


KIT PART NO.	DESCRIPTION	COUPLER	PLUG	ORDER NO.	PRICE EACH
S-772	A style coupler & plug combo	(1) 775	(1) 777	3350-458	\$10.61
S-213	A style coupler & plug kit - 5 pc.	(1) 775	(3) 777, (1) 778	3350-071	\$15.69



1875



1877



1878

Ctn. Qty.: 5

### "AA 310" STYLE 3/8" BASIC SIZE


NPT THREAD	FEMALE	ORDER NO.	PRICE EACH	MALE	ORDER NO.	PRICE EACH
<b>COUPLERS</b>						
3/8"	1875	3351-048	\$16.27	-	-	-
<b>PLUGS</b>						
3/8"	1878	3351-050	\$3.49	1877	3351-049	\$3.15

## AA-ARO 310 Style Couplers & Plugs


- AA-style couplers are push type
- AA-style coupler bodies are heavy duty steel
- AA-style plugs are case hardened steel, plated to resist rust
- Maximum inlet pressure: 300 PSI
- Maximum temperature: 250° F
- Air flow: 59 SCFM
- Seals: Buna-N

**WARNING: COUPLERS IN THIS SECTION ARE FOR USE WITH SHOP AIR ONLY.**


## Tru-flate (Automotive) Interchange Series



S-785



S-786



786-4

Ctn. Qty.: 10

### "T" STYLE 1/4" BASIC SIZE

NPT THREAD	FEMALE	ORDER NO.	PRICE EACH	MALE	ORDER NO.	PRICE EACH	BARB	ORDER NO.	PRICE EACH
<b>COUPLERS</b>									
1/4"	S-785	3350-490	\$7.69	S-786	3350-493	\$7.95	786-4	3350-495	\$9.36
3/8"	788	3350-499	\$9.07	789	3350-500	\$8.54	786-6	3350-496	\$9.92

## T Style Couplers & Plugs

- T-style coupler bodies are brass
- T-style plugs are case hardened steel, plated to resist rust
- Maximum inlet pressure: 300 PSI
- Maximum temperature: 250° F
- Air flow: 40 SCFM
- Seals: Buna-N

**WARNING: COUPLERS IN THIS SECTION ARE FOR USE WITH SHOP AIR ONLY.**

# Air Couplers & Plugs



## Tru-flate (Automotive) Interchange Series (Continued)



S-784



S-783

**"T" STYLE 1/4" BASIC SIZE**

Ctn. Qty.: 10 Male/Female: 2/cd

NPT THREAD	FEMALE	CARD PACK	ORDER NO.	PRICE PER CARD	MALE	CARD PACK	ORDER NO.	PRICE PER CARD
<b>PLUGS</b>								
1/4"	S-784	2	3350-487	\$3.41	S-783	2	3350-482	\$3.27
<b>T-STYLE 1/4" COUPLER &amp; PLUG COMBOS AND KITS</b>								
KIT PART NO.	DESCRIPTION	COUPLER	PLUG	ORDER NO.	PRICE EACH			
S-782	T style coupler & plug combo	(1) 785	(1) 783	3350-480	\$9.39			
S-215	T style coupler & plug kit - 5 pc.	(1) 785	(3) 783, (1) 784	3350-072	\$14.22			


### T Style Couplers & Plugs

- T-style coupler bodies are brass
- T-style plugs are case hardened steel, plated to resist rust
- Maximum inlet pressure: 300 PSI
- Maximum temperature: 250° F
- Air flow: 40 SCFM
- Seals: Buna-N

**WARNING: COUPLERS IN THIS SECTION ARE FOR USE WITH SHOP AIR ONLY.**



S-1807



S-1808



1807-6

**"P" STYLE 3/8" BASIC SIZE**

Ctn. Qty.: 10 Male/Female: 2/cd

NPT THREAD	FEMALE	CARD PACK	ORDER NO.	PRICE PER CARD	MALE	CARD PACK	ORDER NO.	PRICE PER CARD	BARB	ORDER NO.	PRICE EACH
<b>PLUGS</b>											
1/4"	S-1810	2	3350-973	\$5.82	S-1809	2	3350-970	\$5.69	-	-	-
3/8"	S-1808	2	3350-967	\$6.35	S-1807	2	3350-963	\$6.28	1807-6	3350-965	\$4.05


### P Style Couplers & Plugs

- P-style coupler bodies are heavy duty steel
- P-style plugs are case hardened steel plated to resist rust
- Bodies have 8 locking balls
- Maximum inlet pressure: 300 PSI
- Maximum temperature: 250° F
- Air flow: 68 SCFM
- Seals: Buna-N


**WARNING: COUPLERS IN THIS SECTION ARE FOR USE WITH SHOP AIR ONLY.**



S-1803



1804



1806-6

**"P" STYLE 3/8" BASIC SIZE**

NPT THREAD	FEMALE	ORDER NO.	PRICE EACH	MALE	ORDER NO.	PRICE EACH	BARB	ORDER NO.	PRICE EACH
<b>COUPLERS</b>									
1/4"	S-1803	3350-950	\$15.32	1804	3350-952	\$14.82	-	-	-
3/8"	S-1805	3350-955	\$15.56	S-1806	3350-958	\$15.51	1806-6	3350-960	\$18.25

Ctn. Qty.: 5

### Push Button Safety Couplers

Double click to engage properly. First click locks coupler and plug; the second click engages the air pressure. To disconnect, push button twice. First push relieves pressure; second push allows plug and coupler to be disengaged.



S-99705



S-99706



S-99773



S-99774

Ctn. Qty.: 5

**SAFETY COUPLERS**


PART NO.	THREAD TYPE	STYLE	NPT SIZE	ORDER NO.	PRICE EACH
S-99705	Female	M	1/4"	3351-355	\$17.37
S-99706	Male	M	1/4"	3351-356	17.51
S-99773	Female	A	1/4"	3351-357	17.70
S-99774	Male	A	1/4"	3351-358	17.77

### G Style Couplers & Plugs (Tru-flate/Automotive)


- G-style coupler bodies are steel plated to resist rust
- G-style plug bodies are case hardened steel to resist rust

- Maximum inlet pressure: 300 PSI
- Air flow: 99 SCFM
- Maximum temperature: 250° F
- Seals: Buna-N

**WARNING: COUPLERS IN THIS SECTION ARE FOR USE WITH SHOP AIR ONLY.**



S-1813



Ctn. Qty.: 5

**"G" STYLE 1/2" BASIC SIZE**

NPT THREAD	FEMALE	ORDER NO.	PRICE EACH	MALE	ORDER NO.	PRICE EACH
<b>COUPLERS</b>						
3/8"	1813	3350-976	\$18.32	1814	3350-977	\$18.07
1/2"	S-1815	3350-979	\$18.97	S-1816	3350-982	\$18.85



S-1818



S-1817

Ctn. Qty.: 5

**"G" STYLE 1/2" BASIC SIZE**


NPT THREAD	FEMALE	ORDER NO.	PRICE EACH	MALE	ORDER NO.	PRICE EACH
<b>PLUGS</b>						
3/8"	1820	3350-992	\$4.72	1819	3350-990	\$4.10
1/2"	S-1818	3350-988	\$5.55	S-1817	3350-985	\$4.76



# Air Couplers & Plugs



## V-Style Hi-Flow Interchange Series




S-764

S-765

Ctn. Qty.: 10

"V"STYLE 1/4" BASIC SIZE						
NPT THREAD	FEMALE	ORDER NO.	PRICE EACH	MALE	ORDER NO.	PRICE EACH
<b>COUPLERS</b>						
1/4"	S-764	3350-450	\$7.89	S-765	3350-452	\$7.89
3/8"	S-766	3350-454	8.86	S-767	3350-456	8.86



S-761-1

S-760-1

Ctn. Qty.: 10, 2/cd

"V"STYLE 1/4" BASIC SIZE								
NPT THREAD	FEMALE	CARD PACK	ORDER NO.	PRICE PER CARD	MALE	CARD PACK	ORDER NO.	PRICE PER CARD
<b>PLUGS</b>								
1/4"	S-761-1	2	3350-440	\$3.49	S-760-1	2	3350-436	\$3.39
3/8"	S-763-1	2	3350-448	5.43	S-762-1	2	3350-444	5.31

## V Style Couplers & Plugs

- V-style specifically designed for HVLP (High Volume Low Pressure) applications.
- V-style couplers will accept "M" and "A" style plugs, however to retain max. flow, use "V" style plugs
- V-style couplers are push-type
- Maximum inlet pressure: 300 PSI
- Maximum temperature: 250° F
- Air flow: 74 SCFM
- Seals: Buna-N

**WARNING: COUPLERS IN THIS SECTION ARE FOR USE WITH SHOP AIR ONLY.**



S-764

S-760-1

"V"STYLE 1/4" BASIC SIZE					
KIT NO.	DESCRIPTION	COUPLER	PLUG	ORDER NO.	PRICE EACH
<b>V-STYLE 1/4" COUPLER &amp; PLUG COMBOS AND KITS</b>					
S-216	1/4" V style coupler & plug combo	(1) 764	(1) 760-1	3350-073	\$10.03
S-217	1/4" V style coupler & plug kit- 6 pc.	(2) 764	(2) 760-1, (2) 761-1	3350-074	\$22.25

## Lincoln Interchange Series - L Style Couplers & Plugs

- L-style couplers are push type
- L-style plugs are case hardened steel, plated to resist rust
- L-style couplers are steel, plated to resist rust
- Maximum inlet pressure: 300 PSI
- Maximum temperature: 250° F
- Air flow: 32 SCFM
- Seals: Buna-N

**WARNING: COUPLERS IN THIS SECTION ARE FOR USE WITH SHOP AIR ONLY.**




S-790

794

Ctn. Qty.: 10

"L"STYLE 1/4" BASIC SIZE						
NPT THREAD	FEMALE	ORDER NO.	PRICE EACH	MALE	ORDER NO.	PRICE EACH
<b>COUPLERS</b>						
1/4"	S-790	3350-502	\$14.22	794	3350-510	\$15.15



S-792

S-791

Ctn. Qty.: 10, 2/cd

"L"STYLE 1/4" BASIC SIZE								
NPT THREAD	FEMALE	CARD PACK	ORDER NO.	PRICE PER CARD	MALE	CARD PACK	ORDER NO.	PRICE PER CARD
<b>PLUGS</b>								
1/4"	S-792	2	3350-508	\$5.20	S-791	2	3350-505	\$5.04

## AMT-Style Interchange Series - 3-Way Couplers

- AMT-style are push type with drag guard
- Heavy duty brass-rust resistant
- Accepts the 3 most popular 1/4" basic style plugs sold
  - 1- Milton or industrial style plugs (M-style)
  - 2- Aro 210-style plugs (A-style)
  - 3- Tru-Flate/Parker automotive style plugs (T-style)

**WARNING: COUPLERS IN THIS SECTION ARE FOR USE WITH SHOP AIR ONLY.**



S-745

S-746

Ctn. Qty.: 10

"AMT"STYLE 1/4" BASIC SIZE						
NPT THREAD	FEMALE	ORDER NO.	PRICE EACH	MALE	ORDER NO.	PRICE EACH
<b>COUPLERS</b>						
1/4"	S-745	3350-424	\$12.46	S-746	3350-427	\$12.77

## Straight Thru Couplers & Plugs

- Straight thru couplers are brass with stainless steel balls and spring
- Straight thru plugs are case hardened steel, plated to resist rust
- Compatible with other major manufacturers of straight thru couplers
- Application: high pressure washers, industrial carpet cleaning



1765

1762

1764

1763

STRAIGHT THRU 1/4" & 3/4" BASIC SIZE

Ctn. Qty.: 10


NPT THREAD	FEMALE	ORDER NO.	PRICE EACH	MALE	ORDER NO.	PRICE EACH
<b>COUPLERS</b>						
1/4"	1761	3350-919	\$10.10	1762	3350-921	\$10.31
3/8"	1765	3350-927	POA	1766	3350-929	POA
<b>PLUGS</b>						
1/4"	1764	3350-925	\$2.90	1763	3350-923	\$2.21
3/8"	1768	3350-933	4.03	1767	3350-931	4.48



# TECH TIPS


## BUILDING AN EFFICIENT AIR SYSTEM

Compressed air powered equipment and machinery are critical elements in the productivity, efficiency, and economy of today's industry and quality air is the essential element. Water and dirt cause more problems in compressed air lines than anything else. High speed pneumatic production lines operate efficiently because of air dryers and filters that remove moisture and impurities from the air, which results in eliminating downtime. Regulators and lubricators can be added to control and lubricate downstream equipment. A good air system is the key to saving time, money and to operating at maximum efficiency.



### 5 IMPORTANT STEPS TO AN AIR SYSTEM SETUP

1. Main line filter and regulator should be placed at least 20 feet from the compressor. The air will cool down, allowing much of the water vapor to condense naturally for removal by filtration.
2. Main line piping should slope down from point of origin by 1/8" per foot. Any water in the line will flow down to the lowest point for draining.
3. All line drops (work stations) should be taken from the top of the main line. This prevents water from flowing into branch lines.
4. Galvanized pipe is recommended when building an air system.
5. Follow illustration to the right when building a work station drop.



## Micro Filters



1018



1018-8

- All micro filters supplied with preassembled AUTOMATIC OVERNIGHT DRAIN
- Porous bronze 40 micron filter element allows less pressure drop and longer cleaning intervals
- Safety metal bowl guards or metal bowls standard on 1/4", 3/8", 1/2" models
- Metal bowls only on 3/4" and 1" models
- 3 stage baffle system for exceptional moisture removal.
- Sintered bronze elements are permanent and cleanable
- Light weight aluminum die-cast housing
- Element range 10 or 40 microns exactly matching filter and air flow needs
- Corrosion resistant metal bowls
- 1022-8 and 1022-10 include sight glass for visual check of condensation collection

### MICRO & MINI FILTERS

PART NO.	NPT	ORDER NO.	PRICE EACH	BOWL TYPE	BOWL CAPACITY	MAX. SCFM	MAX INLET PSI	TEMP. OP. RANGE	FILTER ELEMENT(MICRON)
1018	1/4"	3350-552	\$64.02	POLY w/GUARD	5 OZ	48	150	40°F-120°F	40, 10 opt.
1018-8	1/4"	3350-554	75.67	METAL	6 OZ	48	250	40°F-160°F	40, 10 opt.
1019	3/8"	3350-557	64.35	POLY w/ GUARD	5 OZ	75	150	40°F-120°F	40, 10 opt.
1019-8	3/8"	3350-559	75.67	METAL	6 OZ	75	250	40°F-160°F	40, 10 opt.
1020	1/2"	3350-560	65.59	POLY w/ GUARD	5 OZ	100	150	40°F-120°F	40, 10 opt.
1020-8	1/2"	3350-562	75.28	METAL	6 OZ	100	250	40°F-160°F	40, 10 opt.
1022-8	3/4"	3350-563	150.63	METAL	10 OZ	230	250	40°F-160°F	40
1022-10	3/4"	3350-564	233.27	METAL	20 OZ	245	250	40°F-160°F	40
1120-8	1/2"	3350-682	102.34	METAL	9 OZ	115	250	40°F-160°F	40
1122-8	1"	3350-683	174.35	METAL	29 OZ	300	250	40°F-160°F	40
S-1144	1/4"	3350-694	42.02	POLY	1 OZ	27	150	40°F-120°F	20
1144 M	1/4"	3350-697	51.50	METAL	1 OZ	27	250	40°F-120°F	20

### REPAIR PARTS

MICRO FILTER PART NO.	BOWL KIT	ORDER NO.	PRICE EACH	FILTER (40 MICRON)	ORDER NO.	PRICE EACH	FILTER (10 MICRON)	ORDER NO.	PRICE EACH
1018	1018-P	3350-556	\$38.01	1118-1	3350-679	\$15.21	1118-2	3350-680	\$17.61
1018-8	1018-M	3350-555	61.11	1118-1	3350-679	15.21	1118-2	3350-680	17.61
1019	1018-P	3350-556	38.01	1118-1	3350-679	15.21	1118-2	3350-680	17.61
1019-8	1018-M	3350-555	61.11	1118-1	3350-679	15.21	1118-2	3350-680	17.61
1020	1018-P	3350-556	38.01	1118-1	3350-679	15.21	1118-2	3350-680	17.61
1020-8	1018-M	3350-555	61.11	1118-1	3350-679	15.21	1118-2	3350-680	17.61
1022-8	-	-	-	P1022-18	3351-364	23.80	-	-	-
1120-8	-	-	-	P1120-17	3351-366	44.50	-	-	-
<b>(20 MICRON)</b>									
S-1144	1152	3350-706	17.17	1144-1	3350-695	10.03	-	-	-
1144 M	-	-	-	1144-1	3350-695	10.03	-	-	-
1144-2	1152	3350-706	17.17	1144-1	3350-695	10.03	-	-	-

**WARNING: FOR COMPRESSED AIR SERVICE ONLY. NOT TO BE USED ON LIFE SUPPORT SYSTEMS OR BREATHING AIRSYSTEMS. NEVER USE POLY-CARBONATE PLASTIC BOWLS ON AIR SUPPLIED BY A COMPRESSOR LUBRICATED WITH SYNTHETIC OILS OR OIL CONTAINING PHOSPHATE ESTERS OR CHLORINATE HYDROCARBONS.**

## Coalescing Filters

An extremely efficient filter designed for applications that require air free of oil and all foreign particles. Effective filtration and low pressure drop make these filters perfect for fluidics, body shop, spray painting, food processing, instrumentation and pharmaceuticals.

- Automatic overnight drain
- Metal bowl
- .03 SUB-MICRON = 99.97 efficiency
- 1037-8 includes sight glass for visual check of condensation collection



1035



1037-8

### COALESCING FILTERS

PART NO.	NPT	ORDER NO.	PRICE EACH	BOWL TYPE	BOWL CAPACITY	MAX. SCFM	MAX INLET PSI	TEMP. OP. RANGE	FILTER ELEMENT(MICRON)
1035	1/4"	3350-581	\$145.07	METAL	6 OZ	24	250	40°F-200°F	.03 Sub micron
1036	3/8"	3350-582	145.93	METAL	6 OZ	37	250	40°F-200°F	.03 Sub micron
1037	1/2"	3350-583	145.76	METAL	6 OZ	37	250	40°F-200°F	.03 Sub micron
1037-8	3/4"	3350-584	217.05	METAL	10 OZ	60	250	40°F-160°F	.03 Sub micron

### REPAIR PARTS

COALESCING FILTER PART NO.	BOWL KIT	ORDER NO.	PRICE EACH
1035	1018-M	3350-555	\$61.11
1036	1018-M	3350-555	61.11
1037	1018-M	3350-555	61.11

## Mid-Size & Heavy Duty Regulators

The Milton heavy duty and mid-size RELIEVING TYPE regulators offer stable downstream air pressure over a wide range of air flows with accurate control, fast response and minimal pressure drop. Offset 1/4" gage ports can also serve as two 1/4" supply lines, allowing up to three regulated full flow out ports. Gage not included, but available as an accessory.

**WARNING: REGULATORS SHOULD ALWAYS BE PRECEDED BY A FILTER TO ELIMINATE DAMAGE TO THE UNIT OR INACCURATE AIR FLOW.**

- Inlet pressure: 250 PSI
- Operating temperature: 40° F to 120° F
- Aluminum die-cast body
- Buna-N diaphragm and O rings
- Balanced piston, molded rubber seat



1113



S-1145

### MID-SIZE & HEAVY DUTY REGULATORS

PART NO.	NPT	ORDER NO.	PRICE EACH	MAX. SCFM	OP. RANGE PSI	MAX INLET PSI	GAGE PORT NPT	TEMP. OP. RANGE
1113	1/4"	3350-669	\$ 63.50	50	5-125	250	1/4"	40°F-120°F
1113-8	1/4"	3350-671	69.06	50	10-250	250	1/4"	40°F-120°F
1114	3/8"	3350-673	63.80	80	5-125	250	1/4"	40°F-120°F
1114-8	3/8"	3350-675	69.06	80	10-250	250	1/4"	40°F-120°F
1115	1/2"	3350-676	78.77	100	5-125	250	1/4"	40°F-120°F
1115-8	1/2"	3350-678	85.52	100	10-250	250	1/4"	40°F-120°F
1026	3/4"	3350-565	104.94	220	5-125	250	1/4"	40°F-120°F
1026-8	3/4"	3350-566	111.41	220	10-250	250	1/4"	40°F-120°F
1027	1"	3350-567	141.02	250	5-125	250	1/4"	40°F-120°F
1027-8	1"	3350-568	152.21	250	10-250	250	1/4"	40°F-120°F
S-1145	1/4"	3350-698	39.26	25	5-125	250	1/8"	40°F-120°F
S-1146	1/4"	3350-702	37.42	25	0-60	250	1/8"	40°F-120°F
1145-2	1/8"	3350-701	39.51	25	5-125	250	1/8"	40°F-120°F

## Precision Lubricators

Ideal for the customer who wants trouble-free protection and tamper proof reliability. Drop style allows precise setting and then removal of adjustment knob. Perfect for lubrication of air motors, tools, valves or where low air flow is encountered or where extremely fine adjustments are necessary.

**WARNING: POLYCARBONATE BOWLS CAN BE CHEMICALLY ATTACKED AND RUPTURE. CHECK INSTRUCTION SHEET WITH EACH LUBRICATOR FOR LIST OF KNOWN HARMFUL CHEMICALS.**

- Sight glass dome on drop type allows observation for instant drip rate adjustment
- Tamper proof
- Lubricator may be filled without shutting down line pressure
- Oil supply tube check valve guarantees INSTANT START-UP LUBRICATION
- Low pressure drop at full air flow
- Oil delivered at an air flow as low as 2 SCFM



1028



1028-8



S-1150

### PRECISION LUBRICATORS

PART NO.	NPT	ORDER NO.	PRICE EACH	BOWL TYPE	BOWL CAPACITY	MAX. SCFM	MAX INLET PSI	TEMP. OP. RANGE	TYPE
1028	1/4"	3350-569	\$80.21	POLY W/ GUARD	5 OZ	16	150	40°F-125°F	DROP
1028-8	1/4"	3350-571	89.72	METAL	6 OZ	16	200	40°F-160°F	DROP
1029	3/8"	3350-574	84.16	POLY W/ GUARD	5 OZ	82	150	40°F-125°F	DROP
1029-8	3/8"	3350-576	90.05	METAL	6 OZ	82	200	40°F-160°F	DROP
1030	1/2"	3350-577	80.38	POLY W/ GUARD	5 OZ	142	150	40°F-125°F	DROP
1030-8	1/2"	3350-579	89.61	METAL	6 OZ	142	200	40°F-160°F	DROP
1031-8	1/2"	3350-580	105.12	METAL	9 OZ	142	200	40°F-160°F	DROP
1131-9	3/4"	3350-684	131.89	METAL	10 OZ	142	250	40°F-160°F	DROP
1131-10	3/4"	3350-685	227.74	METAL	20 OZ	142	250	40°F-160°F	DROP
1132-8	1"	3350-686	174.35	METAL	29 OZ	175	250	40°F-160°F	WICK
S-1150	1/4"	3350-703	64.07	POLY	1 OZ	16	150	40°F-120°F	DROP
1150 M	1/4"	3350-705	78.61	METAL	1 OZ	16	150	40°F-120°F	DROP

### REPAIR PARTS

LUBRICATOR PART NO.	BOWL KIT	ORDER NO.	PRICE EACH
1028	1028-P	3350-573	\$36.08
-	-	-	-
1029	1028-P	3350-573	36.08
-	-	-	-
1030	1028-P	3350-573	36.08
-	-	-	-
-	-	-	-
-	-	-	-
-	-	-	-
-	-	-	-
S-1150	1152	3350-706	17.17



## Piggyback Filter/Regulator

Piggyback duo has the features of the standard regulator, plus the space saving convenience of a combined filter. Gage not included, but available as an accessory.

- Non-rising adjustment
- 3 position knob lock/adjust/remove

REPAIR PARTS						
FILTER/REG. PART NO.	BOWL KIT	ORDER NO.	PRICE EACH	FILTER	ORDER NO.	PRICE EACH
S-1142	1152	3350-706	\$17.17	1144-1	3350-695	\$10.03
1142-1	1152	3350-706	17.17	1144-1	3350-695	10.03



1109

### PIGGYBACK FILTERS/REGULATORS

PART NO.	NPT	FILTER ORDER NO.	AUTO PRICE EACH	BOWL TYPE	BOWL CAPACITY	MAX. SCFM	OPEN RANGE PSI	MAX INLET PSI	TEMP. OP. RANGE	ELEMENT (MICRON)	OVERN'T DRAIN
1109	1/4"	3350-663	\$130.79	METAL	6 OZ	50	2-125	200	40°F-160°F	40	YES
1110	3/8"	3350-665	131.27	METAL	6 OZ	80	2-125	200	40°F-160°F	40	YES
1111	1/2"	3350-667	131.80	METAL	6 OZ	100	2-125	200	40°F-160°F	40	YES
S-1142	1/4"	3350-691	88.63	POLY	1 OZ	25	0-125	150	40°F-120°F	20	YES
1142-1	1/8"	3350-692	95.59	METAL	1 OZ	25	0-125	150	40°F-120°F	20	YES

## Deluxe F-R Duo

- Factory assembled
- Automatic overnight drains
- Relieving regulator
- Complete with gage #1191
- 40 micron filter element
- Outlet pressure range: 2-125 PSI
- Temperature range: 40° F to 150° F



1106

## Deluxe F-R-L Trios

- Filter has automatic overnight drain
- Relieving regulator, drop style lubricator
- Complete with gage #1191
- 40 micron filter element
- Outlet pressure range: 2-125 PSI
- Temperature range: 40° F to 150° F



1100

### DELUXE F-R DUO

MILTON PART. NO.	NPT	BOWL TYPE	MAX SCFM	MAX PSI	ORDER NO.	PRICE EACH
1106	1/4"	Poly with metal guard	48	150	3350-660	\$156.98
1107	3/8"	Poly with metal guard	75	150	3350-661	161.88
1108	1/2"	Metal bowl	100	250	3350-662	176.96

### DELUXE F-R-L TRIOS

MILTON PART. NO.	NPT	BOWL TYPE	FACTORY ASSEMBLED	MAX SCFM	MAX PSI	ORDER NO.	PRICE EACH
1100	1/4"	Poly with metal guard	Yes	16	150	3350-657	\$236.59
1101	3/8"	Poly with metal guard	Yes	80	150	3350-658	235.49
1102	1/2"	Metal bowl	No	100	250	3350-659	270.23

## Deluxe Mini F-R-L Trio



S-1140

When space is a problem we recommend the mini filter-regulator-lubricator which offers most of the same features as our full size units. Comes pre-assembled with 0-160 PSI gage (#1189). Length: 5 1/4" x height: 6 1/2". Maximum SCFM 20.

MILTON PART. NO.	DESCRIPTION	ORDER NO.	PRICE EACH
S-1140	1/4" NPT Filter, Regulator, Lubricator	3350-690	\$157.42

# Compressor Accessories



## Pressure Gages

Milton high quality dry gages for reliable service with compressors, filters-regulators-lubricators, air lines, pneumatic tools & equipment.

- Resistant to heat, corrosion, water, salt water, and oil
- Can be used in steam applications if less than 120° F
- Brass mechanism. ABS case. Polycarbonate lens
- Maximum working pressure: Should be limited to 75% of dial range
- Maximum working temperature: -13° F to +120° F



1193

MILTON PART. NO.	NPT	MOUNT	PSI RANGE	FACE	ORDER NO.	PRICE EACH
1188	1/8"	Mini center back	0-60 PSI	1 1/2"	3350-724	\$21.57
1189	1/8"	Mini center back	0-160 PSI	1 1/2"	3350-725	21.47
1190	1/4"	Center back	0-60 PSI	2"	3350-726	18.27
1191	1/4"	Center back	0-160 PSI	2"	3350-727	18.11
1192	1/4"	Center back	0-300 PSI	2"	3350-728	18.18
1193	1/4"	Bottom	0-60 PSI	2"	3350-729	18.27
1194	1/4"	Bottom	0-160 PSI	2"	3350-730	18.11
1195	1/4"	Bottom	0-300 PSI	2"	3350-731	18.18

## Compressor Pressure Switches

Furnace universal pressure switches are suitable to replace pressure switches on compressors up to: 2 HP @ 120V 1 phase, 3 HP @ 240V 1 phase or 5 HP @ 240V 3 phase. Combination terminals can be used with quick connects (slip on terminals) or standard screw terminals. Auto-off disconnect lever and rotating unloader valve for applications requiring these modifications. Four 1/4" NPT female port manifold complete with plugs. UL listed, CSA certified. Switches are in displayable packaging.

S-1060 PRESSURE SWITCH 95-125 PSI  
Order No. 3350-591 ...Price Each: \$77.14

S-1062 PRESSURE SWITCH 140-175 PSI  
Order No. 3350-592 ...Price Each: \$77.95



S-1060

## Pneumatic Exhaust Mufflers

Muffler-filters use a porous sintered bronze, bonded to a copper plated steel pipe threaded fitting. These 40 micron exhaust mufflers diffuse air and muffle noise from exhaust ports of air tools, cylinders and valves to an acceptable OSHA noise requirements.

- Maximum operating pressure: 300 PSI
- Operating temperatures: 40° F to 300° F




S-1086-2

Ctn. Qty.: 5

MILTON PART. NO.	SIZE	LENGTH	HEX	WEIGHT (LBS.)	CTN. QTY.	ORDER NO.	PRICE EACH
S-1086-2	1/8" NPT	1 1/8"	7/16"	.02	5	3350-603	\$6.62
S-1086-4	1/4" NPT	1 3/8"	9/16"	.04	5	3350-606	7.27
S-1086-6	3/8" NPT	1 1/2"	9/16"	.05	5	3350-609	9.37
1086-8	1/2" NPT	1 7/8"	7/8"	.10	-	3350-611	8.22

## ASME Coded Safety Valves




S-1090-70

Valves are manufactured to ASME standards and certified by the national board of boiler and pressure vessel inspectors. Bubble tight to 10% of set pop-off pressure. Milton ASME safety valves are interchangeable with all other ASME valves of same size and pressure. 2" length.

MILTON PART. NO.	MALE NPT	POP-OFF PRESSURE	AIR FLOW POP-OFF PSI	ORDER NO.	PRICE EACH
S-1090-70	1/4"	70 PSI	70 CFM	3350-621	\$16.97
S-1090-125	1/4"	125 PSI	120 CFM	3350-623	16.83
S-1090-150	1/4"	150 PSI	140 CFM	3350-625	16.83
S-1090-200	1/4"	200 PSI	170 CFM	3350-627	16.83

## Full Port Brass Ball Valves

These high capacity ball valves are designed for use with compressed air, water or oil to isolate segments of the system without disrupting service to the rest of the system. All brass body with plated steel ball, teflon seals, plated 1/4 turn handle.



S-1094-4

- Maximum working pressure air, water, oil: 400 PSI
- Maximum working pressure steam: 150 PSI
- Temperature: -20° F to 350° F

MILTON PART. NO.	FEM. X FEM NPT	BODY LENGTH	MAX PRESSURE AT 210° F (PSI)	ORDER NO.	PRICE EACH
S-1094-4	1/4" x 1/4"	1 3/4"	280	3350-642	\$17.26
S-1094-6	3/8" x 3/8"	1 3/4"	260	3350-644	20.89
S-1094-8	1/2" x 1/2"	2 1/2"	250	3350-646	22.14
1094-12	3/4" x 3/4"	2 1/2"	220	3350-647	35.79
1094-16	1" x 1"	3 1/4"	190	3350-648	43.80

## Breather Vents

Offer vacuum relief or pressure equalization on gear boxes, oil tanks or reservoirs. Prevents dirt and particles from entering open ports. 40 micron units have standard pipe thread for quick assembly or removal.

- Maximum working pressure: 150 PSI
- Operating temperatures: 35° F to 300° F



S-1088-6

MILTON PART. NO.	MALE NPT SIZE	CTN. QTY.	ORDER NO.	PRICE EACH
1088-2	1/8"	10	3350-613	\$2.71
S-1088-4	1/4"	10	3350-615	3.68
S-1088-6	3/8"	5	3350-617	4.85
S-1088-8	1/2"	5	3350-619	5.92



Milton "safety" blo-guns in this section meet OSHA requirements of special relief holes in nozzle which limits pressure to 30 PSI when dead ended (static pressure). For use on regulated compressed air lines maximum PSI 150. Always use personal protective equipment such as safety goggles and ear protection.

## Safety Button Blo-Gun

Compact hand held unit can be used anywhere with compressed air. Streamlined comfort fit and full volume control. Many uses such as cleaning fuel and oil lines, or air cleaners, drying out wet ignition systems and spark plugs or blowing out dirt filings and metal chips.

- Maximum working pressure: 150 PSI
- Maximum nozzle pressure: 30 PSI when dead ended
- SCFM 11.4 @ 100 PSI
- 1/4" NPT air inlet, nozzle thread 5/16"-24
- Zinc die cast body
- OSHA compliant


**S-107 SAFETY BUTTON BLO-GUN**  
Order No. 3350-012 Price Each: \$11.95



## Siphon Spray Blo-Gun

Excellent for degreasing engines, garage bays and parts, spraying livestock, plants and flowers. Perfect for rust proofing tools and machinery and lubricating parts and engines. Kit comes complete with #156 siphon blo-gun, 8' of tubing, and displayable vinyl storage pouch.

**S-156 SIPHON SPRAY BLO-GUN**  
Order No. 3350-045  
Price Each: \$19.88



- Maximum working pressure: 150 PSI
- SCFM 14.0 @ 100 PSI
- 1/4" NPT air inlet

**S-157 SIPHON SPRAY BLO-GUN KIT**  
Order No. 3350-046  
Price Each: \$27.78



## Compact Safety Lever Blo-Gun

Compact and versatile blo-gun comes with both a safety nozzle and rubber tip nozzle. Hang-up hook for easy storage.

- Maximum working pressure: 150 PSI
- SCFM 11.7 @ 100 PSI safety-tip
- SCFM 12.9 @ 100 PSI rubber tip
- 1/4" NPT air inlet
- Zinc die-cast body
- OSHA compliant with safety tip only

**S-148 COMPACT SAFETY LEVER BLO-GUN**  
Order No. 3350-030 Price Each: \$10.98



## Pistol Grip Blo-Gun

Pistol style multi use blo-gun. Accepts Milton #122, 6" ext. and #123, 10" ext.

- Maximum working pressure: 150 PSI • SCFM 10.0 @ 100 PSI
- 1/4" NPT air inlet • Nozzle thread 1/8"-27 NPS
- Zinc die-cast, chrome plated body

**S-160 PISTOL GRIP BLO-GUN**  
Order No. 3350-051 Price Each: \$25.04



## Adjustable Aluminum Pocket Blo-Guns

Easy grip two finger control to adjust from full volume air flow to complete shut off. Knurled grip for secure handling even with oily or greasy fingers. Always keep one handy with included shirt pocket clip. 4 different models to fit popular coupler interchange styles.

- Maximum inlet pressure: 150 PSI
- SCFM 15.9 @ 100 PSI

**S-115 M-style** Fits M-style or any 1/4" Industrial style coupler

Order No. 3350-016 Price Each: \$8.13

**S-116 A-style** Fits A-style or any 1/4" Aro 210 style coupler

Order No. 3350-018 Price Each: \$8.15

**S-117 T-style** Fits T-style or any 1/4" Tru-Flate/Parker style coupler

Order No. 3350-019 Price Each: \$8.15

**S-118 L-style** Fits L-style or any 1/4" Lincoln style coupler

Order No. 3350-020 Price Each: \$9.82



## Lever Hook Blo-Gun

- Max. working pressure: 150 PSI
- Max. nozzle pressure: 30 PSI when dead ended
- SCFM 10.6 @ 100 PSI
- 1/4" NPT air inlet, nozzle thread 1/8"-27
- Zinc die cast body, steel plated handle
- OSHA compliant

**S-120 LEVER HOOK BLO-GUN**  
Order No. 3350-022 Price Each: \$16.09



## Full-Flow Safety Lever Blo-Gun

- Maximum working pressure: 150 PSI • SCFM 10.0 @ 100 PSI
- 1/4" NPT air inlet, nozzle thread size: 7/16"-27
- Body outlet thread size 1/2"-27
- OSHA compliant

**S-150 FULL FLOW SAFETY LEVER BLO-GUN**  
Order No. 3350-034 Price Each: \$15.90



## Brass Extensions

Fits most blo-guns with nozzle thread of 1/8" NPS including Milton numbers 120, S 120, S160

**122 - 6" BLO-GUN EXTENSION**  
No. 3350-024 Price: \$14.15


**123 - 10" BLO-GUN EXTENSION**  
No. 3350-025 Price: \$18.13



## Rubber Tip Blo-Guns

- 1/4" NPT air inlet. Rubber tip

**S-153 LEVER BLO-GUN**  
Order No. 3350-041 Price Each: \$15.97



- 1/4" NPT air inlet.
- Rubber tip. 45° bent tube is ideal for automatic transmissions
- Maximum working pressure: 150 PSI
- SCFM 11.4 @ 100 PSI

**S-154 LEVER BLO-GUN** Ctn. Qty.: 5  
Order No. 3350-043 Price Each: \$17.75



**151 CONTROL VALVE** Ctn. Qty.: 10  
Order No. 3350-036 Price Each: \$12.73

151




## Pistol Grip Blo-Gun Kit


Safety Tip Nozzle & KWIK-CHANGE® Universal Tip System (4-Piece)

- PISTOL GRIP BLOW GUN: Contoured grip for comfort, easy handling. Simple trigger-controlled air flow.
- INCLUDES: The KWIK-CHANGE® Universal Tip System (Milton # S-168).
- SAFETY TIP: OSHA-Compliant, 4" angled safety nozzle w/side vent. Adjustable flow control knob.
- 90 MAX PSI: 1/4" national pipe thread brass air inlet. 16.5 standard cubic feet per minute.
- EASY STORAGE: Built-in hook/loop for hanging anywhere in your home garage or shop.

**S-174 - KIT PISTOL GRIP BLOW GUN KIT**  
Order No. 3351-654 Price Each: \$23.07



## Ultra® Venturi Safety Air Gun - Short Trigger



MODEL U75LJ012AA2

Ideal for cleaning inaccessible and hard-to-reach areas. Efficient venturi nozzle boosts thrust up to 300% over conventional air guns, yet limits static pressure to less than 30 psi should the tip become blocked. Ergonomic, cushioned pistol-grip style handle provides unparalleled comfort.

- Cast aluminum body with premium cushion grip
- Ergonomic trigger
- Adjustable hanging hook
- Aluminum extension
- Zinc alloy venturi nozzle
- 3/8" FNPT inlet
- Meets OSHA Standards
- Thrust: 2.8 lbs.
- Noise: 104 dB • Air Usage: 49 cfm

GUARDAIR PART. NO.	DESCRIPTION	WEIGHT/ LBS.	ORDER NO.	PRICE EACH
U75LJ012AA2	w/ 12" Extension	1.2	3355-002	\$62.68

## Long John® Safety Air Guns



MODEL 75LJ006AA



MODEL 75LJX03

The perfect tool for cleaning inaccessible and hard-to-reach areas. Used for blowing floor debris, cleaning masonry forms, tanks, ovens, molds, and rafters, as well as machinery and storage areas. Efficient venturi nozzle boosts thrust up to 200% over conventional air guns, yet limits static pressure to less than 30 psi should the tip become blocked.

- Durable cast aluminum body with hanging hook
- Rugged aluminum extension
- Meets OSHA Standards
- Thrust: 2.0 lbs. • Noise: 107 dB • Air Usage: 34 cfm
- Wide comfort trigger
- Powerful zinc alloy venturi nozzle
- 1/4" FNPT inlet
- Air Usage: 34 cfm

GUARDAIR PART. NO.	DESCRIPTION	WEIGHT/ LBS.	ORDER NO.	PRICE EACH
75LJ006AA	w/ 6" Extension	0.7	3355-161	\$35.96
75LJ012AA	w/ 12" Extension	0.85	3355-162	38.02
75LJ018AA	w/ 18" Extension	0.9	3355-163	40.07
75LJ024AA	w/ 24" Extension	1.02	3355-164	42.13
75LJ036AA	w/ 36" Extension	1.25	3355-165	46.24
75LJ048AA	w/ 48" Extension	1.45	3355-166	50.35
75LJX03	75LJ Assembled Casting	0.4	3355-913	24.66

## Xtra Thrust® Safety Air Guns

Featuring the Xtra Thrust® venturi nozzle, it delivers over 300% more thrust than conventional air guns. Designed for tough, close-in work. Most powerful Guardair bench-top gun. Guardair recommends the use of High Flow connectors for maximum performance.

GUARDAIR PART. NO.	DESCRIPTION	WEIGHT/ LBS.	ORDER NO.	PRICE EACH
75XXT	Xtra Thrust Safety Air Gun	0.75	3355-210	\$35.96
75XT006AA	w/ 6" Extension	0.72	3355-211	41.10
75XT012AA	w/ 12" Extension	0.82	3355-212	43.16
75XT024AA	w/ 24" Extension	1.02	3355-214	47.27
75XT036AA	w/ 36" Extension	1.24	3355-215	51.38
75XT048AA	w/ 48" Extension	1.44	3355-216	55.49



MODEL 75XT006AA

- Durable cast aluminum body
- Rugged hanging hook
- Full length comfort trigger
- Thrust: 2.5 lbs.
- 1/4" FNPT inlet
- Meets OSHA Standards
- Zinc alloy Xtra Thrust® venturi nozzle
- Noise: 108 dB • Air Usage: 54 cfm

## Thumbswitch Safety Air Guns

Compact design fits comfortably in the palm of your hand. Venturi nozzle delivers safe yet powerful thrust.

GUARDAIR PART. NO.	DESCRIPTION	WEIGHT/ LBS.	ORDER NO.	PRICE EACH
900	Safety Air Gun	0.44	3355-290	\$16.44
900LJ012AA	w/ 12" Extension	0.56	3355-312	31.85
900LJ024AA	w/ 24" Extension	0.62	3355-314	35.96



MODEL 900LJ012AA

- Durable, cast aluminum body
- Comfortable, steel trigger
- Aluminum venturi nozzle
- 1/4" FNPT inlet
- Meets OSHA Standards
- Thrust: 1.1 lbs.
- Noise: 97 dB
- Air Usage: 16 cfm

## Compact Thumbswitch Safety Air Gun

GuardAir's most compact design fits comfortably in the palm of your hand. Venturi nozzle delivers safe yet powerful thrust.

- Durable cast zinc body
- Rubber cushioned, steel trigger
- Convenient hanging hook
- Brass venturi nozzle
- 1/4" FNPT inlet
- Meets OSHA Standards
- Thrust: 0.6 lbs. • Weight: 0.35 lbs • Noise: 104 dB • Air Usage: 8 cfm

Model 970 - Order No. 3355-294 Price Each: \$14.39



MODEL 970

## Jet Guard Safety Air Guns

Featuring a proprietary, protective air cone to shield against dangerous "chip fly-back," the 74S and 74SK are perfect for close-in applications.

GUARDAIR PART. NO.	DESCRIPTION	WEIGHT/ LBS.	ORDER NO.	PRICE EACH
74S	Safety Air Gun	0.7	3355-106	\$28.77
74SK	w/ Volume Control	0.7	3355-108	36.99

- Durable cast aluminum body with hanging hook
- Wide comfort trigger
- Safety air shield
- Pinned tamper-proof nozzle
- 1/4" FNPT inlet
- Meets OSHA Standards
- Thrust: 0.4 lbs.
- Noise: 102 dB
- Air Usage: 35 cfm



MODEL 74S



MODEL 74SK



## Whisper Jet® Safety Air Guns

Whisper Jet® nozzle technology to reduce air gun noise. Solid conical tip prevents blockage of nozzle. Ideal for cleaning in noise sensitive areas.

GUARDAIR PART. NO.	DESCRIPTION	WEIGHT/ LBS.	ORDER NO.	PRICE EACH
80WJ	Safety Air Gun	0.64	3355-240	\$33.91
80LJ012AA	w/ 12" Extension	0.82	3355-232	41.10

- Durable cast aluminum body
- Rugged hanging hook
- Powerful aluminum Whisper Jet® silencer nozzle
- 1/4" FNPT inlet
- Meets OSHA Standards
- Thrust: 1.1 lbs.
- Wide comfort trigger
- Noise: 93 dB
- Air Usage: 20 cfm



MODEL 80WJ

## Lazer® Safety Air Guns

Designed to maximize operator comfort and reduce hand fatigue. Integrated hanging hook for intuitive storage and retrieval. Powerful, accurate. Perfect for DIY, automotive, and industrial cleaning applications.

Model LZR600 - Order No. 3355-250 Price Each: \$ 22.61

- Lightweight, all metal construction
- Soft, over-molded rubber, comfort trigger
- Brass venturi nozzle
- 1/4" FNPT inlet
- Meets OSHA Standards
- Thrust: 0.4 lbs.
- Noise: 102 dB
- Air Usage: 35 cfm
- Weight: 0.5 lbs.



MODEL LZR600

## Pistol Grip Safety Air Gun

MODEL LZR650



With a unique, ergonomic, pistol-grip design, the LZR650 provides hours of fatigue-free operation. Integrated hanging eyelet for easy storage and retrieval. Powerful, accurate. Perfect for DIY, automotive, and industrial cleaning applications.

- Lightweight, all metal construction
- Wide, contoured trigger
- Brass venturi nozzle
- 1/4" FNPT inlet
- Meets OSHA Standards
- Weight: 0.5 lbs.
- Thrust: 0.6 lbs.
- Noise: 100 dB
- Air Usage: 8 cfm

Order No. 3355-258 Price Each: \$22.61

## Syphon Spray Gun

MODEL 79SG012



Designed for heavy-duty use, the versatile 79SG012 Syphon Gun is ideal for spraying oils, solvents, insecticides, and coatings. Powerful syphon delivers up to 16 gallons of liquid per hour. Adjustable nozzle tip controls flow and spray pattern.

- Durable cast aluminum body with hanging hook
- Wide comfort trigger
- 1/4" FNPT inlet
- 6', 1/4" ID, clear PVC feed tube with brass sinker
- 12" aluminum extension
- Brass nozzle tip
- Weight: 1.65 lbs.
- Flow rate: 12 gph
- Air Usage: 8 cfm

Order No. 3355-451 Price Each: \$99.67

## Force 5® Series

MODEL F5024AA



The most powerful safety air gun on the planet, the Force 5 Series is designed for heavy-duty industrial and construction cleaning applications. Featuring a dead-man trigger, the Force 5 Series are the safe alternative to dangerous, "home-made," ball valve actuated, open pipes. Engineered to be paired with tow-behind, or large in-plant compressors.

- Rugged, lightweight, pistol-grip style aluminum handle
- Heavy-duty aluminum extension
- Adjustable auxiliary handle
- Weight: 3.9 lbs.
- Venturi and Quiet Force Nozzle options available
- 3/4" FNPT inlet
- Meets OSHA Standards
- Thrust: 13.5 lbs.
- Noise: 121 dB
- Air Usage: 185 cfm

Order No. 3355-384 Price Each: \$293.87

## Pneumatic Vacuums

### MV2000 - 5.5 Gal. Pneumatic Vacuum

Engineered to mount on any vertical surface, the powerful, portable 5.5 gallon MV2000 Pneumatic Vacuum quickly and effectively sucks up debris, metal chips, dirt, sawdust, and fine materials including powders and talc. Also capable of vacuuming liquids such as machine oils, lubricants, and other fluids. Virtually maintenance-free; no moving parts to wear out. With no electric motor to spark or burn out, the Mac Vac eliminates electrical extension cords—potentially dangerous in wet environments and always a tripping hazard.

Order No. 3355-490 Price Each: \$ 1197.33

- 5.5 gal. chemical resistant polyethylene container
- Predrilled, steel mounting plate
- Cartridge filter (77% Efficient @ 0.8 Microns)
- Liquid shut-off and drum drain
- 1-1/2" ID x 10' flexible vacuum hose
- 1-1/2" OD x 11" plastic crevice tool
- 3/8" FNPT inlet

- Vacuum Lift (in H2O): 77
- Vacuum Flow: 73 cfm
- Air Usage: 21 cfm
- Noise Level: 88 dB
- Weight: 13 lbs.



MODEL MV2000

### CS3000 - Personnel Cleaning Station

Running off standard shop compressed air, the Personnel Cleaning Station pairs a proprietary, on-demand air-agitator brush attachment with a high-efficiency pneumatic vacuum. Thumb-switch activated, the air-agitator loosens and lifts particles airborne where the vacuum sucks them away safely and effectively. With no motor to burn out, the Personnel Cleaning Station is virtually maintenance-free. Vertical Mounting System (VMS) mounts on any vertical surface, saving valuable factory floor space.

Order No. 3355-480 Price Each: \$ 1947.32

- 5.5 gal. chemical resistant polyethylene container
- Predrilled, steel mounting plate
- Cartridge filter (77% Efficient @ 0.8 Microns)
- Liquid shut-off and drum drain
- 1-1/2" ID x 10' flexible vacuum hose
- 1-1/2" OD x 11" plastic crevice tool
- 3/8" FNPT inlet

- Vacuum Lift (in H2O): 77
- Vacuum Flow: 73 cfm
- Air Usage: 21 cfm
- Noise Level: 88 dB
- Weight: 13 lbs.



MODEL CS3000

### 1500 - Gun Vac® Kit

Place twice the power of a standard shop vacuum in the palm of your hand. Powered by standard shop compressed air, the lightweight 1500 Gun Vac has no electric motors to burn out. Easy to empty, high filtration collection bag attaches to rear of vacuum via hose cuff. Tapered vacuum inlet accepts all standard 1-1/4" vac accessories. Unit hangs on a hook, ready for use at anytime.

Order No. 3355-460 Price Each: \$ 121.15

- Rugged, all metal construction
- Contoured comfort grip
- Convenient hanging eyelet
- High filtration collection bag with zipper
- 9" crevice tool included
- 1/4" FNPT bottom and rear inlets

- Vacuum Lift (in H2O): 75
- Vacuum Flow: 78 cfm
- Air Usage: 29 cfm
- Weight: 2.1 lbs.



MODEL 1500



## Safety Extension Blo-Gun

OSHA approved multi-punction blo-gun comes with a safety nozzle and rubber tip nozzle. Extension is bent to access hard to reach areas such as motors, machinery, transmissions, combines, and hidden areas. Display packed.



### S-158 2' EXTENSION BLO-GUN

Order No. 3350-047

Price Each: \$32.86

### S-159 4' EXTENSION BLO-GUN

Order No. 3350-049 Price Each: \$36.74

## Rubber Tip For Blo-Guns

For use where leak-proof connection is required when blowing out fluid lines. O-ring seals create an air-tight connection. A must where metal tip could mar delicate finish in molds or paint. Dual thread design permits use on all blo-guns with 7/16"-27 and 1/8" NPS.

### S-152 RUBBER BLO-GUN TIP

Order No. 3350-038

Price Each: \$4.83




## Window Inflator Gage

Heavy duty construction provides long service life even with constant use. Gage cartridge and valve cartridge replaceable. All window inflator gages equipped with magnifying lens for full view of scale.

Model 501: For high pressure truck tires. 10 lbs. to 160 lbs., in 2 lb. increments. Gage complete with a 5' hose with a dual head straight foot chuck for innerduals with lock on threads both ends (full swivel). Built in deflator to relieve excess pressure. Meets OSHA regulation No. 1910.177 on inflation.

### Model 501 WINDOW INFLATOR GAGE

Order No. 3350-173 Price Each: \$98.50



## Truck Inflator Gage With 15' Hose

Newer steel belted sidewall tires on trucks present a potential danger during inflation. Milton's NEW 501 inflator keeps the technician 15' out of harm's way. Heavy duty construction provides long service life even with constant use. Gage & valve cartridges are replaceable. All window inflator gages equipped with magnifying glass for full view of scale.

- 15' hose, 10 -160 PSI
- Built-in deflator to relieve excess pressure
- Dual foot locking chuck
- Heavy duty construction
- Magnifying lens
- Unit pack qty. - 1, wt. 4 lbs.



### 98-A1-501 TRUCK INFLATOR GAGE WITH 15' HOSE

Order No. 3350-174 Price Each: \$127.88

## Filler Faucets

Easy operation and smooth flow due to long flexible rubber spout with lever control. Heavy duty, ruggedly built with stainless steel springs.

- Operating pressure: standard municipal (city) water
- Pressure 30 - 35 psi, nitrile rubber, zinc alloy body



### 209 FEMALE 1/4" NPT THREAD

Order No. 3350-066 Price Each: \$19.36

## Window Inflator Gage Replacement Parts

OSHA approved multi-function blo-gun comes with a safety nozzle and rubber tip nozzle. Extension is bent to access hard to reach areas such as motors, machinery, transmissions, combines, and hidden areas . Display packed.

### 507A REPLACEMENT CARTRIDGE KIT

Order No. 3350-183


Price Each: \$19.08



### 507B INFLATOR GAGE OVERHAUL KIT

Order No. 3350-184

Price Each: \$34.91



### 509 HOSE WHIP ASSEMBLY COMPLETE

Order No. 3350-185

Price Each: \$28.58



### 512A REPLACEMENT VALVE CARTRIDGE

Order No. 3350-188

Price Each: \$11.33



## Repair Parts For Inflator Gages

OSHA approved multi-function blo-gun comes with a safety nozzle and rubber tip nozzle. Extension is bent to access hard to reach areas such as motors, machinery, transmissions, combines, and hidden areas . Display packed.

### 500-4 DUAL HEAD CHUCK

(Free flowing for tire gages only)

Order No. 3350-169

Price Each: \$5.50



### 500-6 STANDARD SIZE WASHER

(For dual head chuck & straight head chuck)

Order No. 3350-170

Price Each: \$0.49



### 500-6 STANDARD SIZE WASHER

(For single head chuck)


Order No. 3350-171

Price Each: \$0.49



## Brass Hose Ferrules

Economical and dependable brass ferrules to make custom hose assemblies. Refer to chart to choose ferrules required for custom sizes.



MILTON PART. NO.	SIZE	HOSE OD	ORDER NO.	PRICE EACH
1654-2	1" x .525 ID	1/2	3350-838	\$0.67
1654-3	1" x .562 ID	9/16	3350-840	0.71
1654-4	1" x .593 ID	19/32	3350-842	0.73
1654-5	1" x .625 ID	5/8	3350-844	0.76
1654-6	1" x .656 ID	21/32	3350-846	0.78
1654-7	1" x .687 ID	11/16	3350-848	0.88
1654-8	1" x .718 ID	23/32	3350-850	0.86
1654-9	1" x .750 ID	3/4	3350-852	0.86
1654-12	1" x .900 ID	7/8	3350-854	0.86

# Tire Gages & Air Chucks



## Air Chucks

WARNING: SEALING TYPE CHUCKS ARE NOT FOR USE ON MILTON INFLATOR GAGES.  
Max: 150 PSI




MILTON PART. NO.	DESCRIPTION	SIZE	ORDER NO.	PRICE EACH
S-690	Dual Head	1/4" female NPT	3350-362	\$9.92
S-691	Straight Head	1/4" female NPT	3350-364	11.62
S-692	Safety Grip Chuck Clip: fits all standard single head air chucks		3350-365	7.64
S-693	Dual Head Straight Foot, for inner duals, ends lock on threads	1/4" female NPT	3350-367	13.79
S-696	Kwik-Grip Safety Chuck	1/4" NPT	3350-372	13.47
S-697	Euro Style Chuck Clip	1/4" ID hose barb	3350-374	18.82
S-698	Chuck Clip w/Female Chuck	1/4" NPT	3350-376	10.41
S-699	Female Single Head Chuck	1/4" NPT	3350-379	3.20

Ctn. Qty.: 10

## Inflator Gage (Window)

Heavy-duty construction provides long service life, even with constant use. Gage/valve cartridges replaceable. All gages equipped with magnifying lens for full view of scale.



**S-506 Gage Complete, Dual Head Chuck (Full Swivel), 15" Hose** S-506  
Order No. 3350-181...Price Each: \$61.60

## Dial Type Tire Gages

- Internal diaphragm construction for greater quality.
- Dial reads in PSI and kPa.
- 45° chuck. • Durable rubber boot.

• Angled single head chuck  
**S-931 0-15 PSI in 1/2 lb increments.**  
Order No. 3351-479...Price Each: \$29.39

• Angled single head chuck  
**S-932 0-60 PSI in 2 lb. increments.**  
Order No. 3351-480...Price Each: \$29.25



## Mini Disposable Air Line Dessicant Filter/Dryer

Removes all traces of dirt, dust, water vapor, oil vapor. Unit ideal for spray guns and applications requiring clean supply of air. 3 3/4" x 1 1/2" size. Light weight 2 oz. Male & female 1/4" NPT ports. See through, non-metallic chemical resistant material. Replace unit when dessicant changes to pink in color.

- Maximum working pressure: 125 PSI
  - Maximum flow capacity: 15 SCFM
  - Working temperature: 32° F to 130° F (0° to 54° C)
  - 2/cd
- S-1173 MINI IN LINE DESICCANT DRYER**  
Order No. 3350-718...Price Per Card: \$35.64



## Pencil Type Pressure Gages

Consumer tire gages are molded of rugged Delrin with strong flexible white NYLON INDICATOR BAR to provide long trouble free life with the same certified accuracy associated with all Milton tire gages. Always check tire pressure when tires are cold. (Ctn. Qty.: 10)

USA made tire gages provide accurate, long life with trouble free performance. Durable plated brass with 4 side nylon indicator bar. Always check tire pressure when tires are cold. (Ctn. Qty.: 10)

**S-917 LOW PRESSURE GAGE IDEAL FOR USE ON ATV'S, GOLF CARTS AND AIR SPRINGS.** Order No. 3350-535...Price Each: \$9.16

• 2 sides 2 to 20 PSI, in 1 lb increments and 2 sides 20 to 140 kPa, in 10 kPa units

**S-920 HIGHER PRESSURE AUTOMOBILE TIRES, including 60** Order No. 3350-536...Price Each: \$8.96

• PSI mini spare tire. Built in tire tread depth gage in 1/16" increments.

• 2 sides 10 to 70 PSI in 2 lb increments and 2 sides 60 to 500 kPa in 10 kPa units

**S-921 PASSENGER CAR TIRE GAGE FOR RADIAL & CONVENTIONAL TIRES.** Order No. 3350-537...Price Each: \$7.54

• 2 sides 5 to 50 PSI in 1 lb increments and 2 sides 40 to 350 kPa in 10 kPa units

**S-923 STRAIGHT CHUCK CAR TIRE GAGE FOR RADIAL & CONVENTIONAL TIRES.** Order No. 3350-538...Price Each: \$8.45

• 2 sides 5 to 50 PSI in 1 lb increments and 2 sides 40 to 350 kPa in 10 kPa units

• 1 lb increments and 2 sides 40 to 350 kPa in 10 kPa units

**S-925 TRUCK, RV, BICYCLE TIRE GAGE.** Order No. 3350-539...Price Each: \$7.81

• 2 sides 20 to 120 PSI in 2 lb increments and 2 sides 120 to 820 kPa in 20 kPa units

**S-927 DUAL CHUCK TRUCK TIRE GAGE.** Order No. 3350-540...Price Each: \$11.42

• 2 sides 20 to 120 PSI in 2 lb increments 2 sides 120 to 820 kPa in 20 kPa units

**S-928 TRACTOR TIRE GAGE FOR AIR/WATER FILLED TIRES.** Order No. 3350-541...Price Each: \$10.70

• 2 sides 5 to 50 PSI in 1 lb increments and 2 sides 40 to 350kPa in 10 kPa units

## Service Gages

Milton precision engineered service gages provide accurate, long life trouble free performance. Plated brass tube and 4 sided nylon indicator bar. Calibrated 2 sides 10 to 160 PSI, in 2 lb increments and 2 sides 80 to 1100 kPa, in 20 kPa units. (Ctn. Qty.: 5)

**S-976 DUAL HEAD CHUCK SERVICE GAGE** Order No. 3350-543...Price Each: \$25.18

**S-986 STRAIGHT FOOT DUAL HEAD CHUCK SERVICE GAGE FOR INNER STYLE DUALS** Order No. 3350-545 ...Price Each: \$29.68



# Hose Ends, Swivels, & In-Line FRL's



## Brass Hose Ends

Brass hose fittings packed 10 per Box. Skin cards bulk packed, fitting quantities check Milton price sheet. NPT=National Pipe Taper (Tapered Thread for general use)

Hose ID = Inside diameter of hose. Hose OD = Outside diameter of hose.



S-600

S-605

Ctn. Qty.: 10, 2/cd

MILTON PART. NO.	DESC.	HOSE ID	THREAD	CARD PACK	ORDER NO.	PRICE PER CARD
S-600	Male	1/4"	1/4" NPT	2	3350-206	\$3.37
S-601	Male	5/16"	1/4" NPT	2	3350-212	3.58
S-602	Male	3/8"	1/4" NPT	2	3350-215	3.86
S-603	Male	3/8"	3/8" NPT	2	3350-218	4.44
S-605	Female, non swivel	1/4"	1/4" NPT	2	3350-224	4.44
S-605-2	Female, non swivel	3/8"	1/4" NPT	2	3350-228	4.49

## Brass Male Full Swivel Fittings



Ctn. Qty.: 5

S-611-6

MILTON PART. NO.	HOSE ID	NPT THREAD	ORDER NO.	PRICE EACH
S-611-6	3/8"	1/4"	3350-240	\$ 5.50

## Brass Hose Menders

Ctn. Qty.: 10, 2/cd




S-640

MILTON PART. NO.	HOSE ID	CARD PACK	ORDER NO.	PRICE PER CARD
S-640	1/4" x 1/4"	2	3350-276	\$4.37
S-641	5/16" x 5/16"	2	3350-279	4.28
S-642	3/8" x 3/8"	2	3350-281	4.33

## Variable Angle Swivel Fittings

Fittings rotate 360° at a 45° angle in any direction virtually eliminating hose twisting and kinking. Rubber dust cover.

- Max. working pressure: 145 PSI
- Temp. range -37° F to 176° F



S-99681-1

S-99681



S-99681-4

Ctn. Qty.: 5

SWIVEL FITTINGS				
PART NO.	NPT SIZE	CONNECTION	ORDER NO.	PRICE EACH
S-99681	1/4" Male NPT	1/4" Male	3351-347	\$9.59
S-99681-1	1/4" Female NPT	1/4" Male	3351-348	9.53
S-99681-4	1/4" M-Style Plug	1/4" Male	3351-351	9.64

## Full Swivel Hose Ends

Ctn. Qty.: 10



S-659

MILTON PART. NO.	MALE NPT SIZE	NPT OR ID	ORDER NO.	PRICE EACH
S-659	1/4"	1/4" NPT female swivel end	3350-331	\$ 11.50

## Reusable Brass Hose Fittings

Note: S-617 may be used with 5/16" hose.

S-617 Ctn. Qty.: 10



MILTON PART. NO.	DESCRIPTION	HOSE OD	HOSE ID	NPT	ORDER NO.	PRICE EACH
S-617	Male end	5/8"	1/4"	1/4"	3350-260	\$4.93
S-621	Male end	3/4"	3/8"	1/4"	3350-264	6.67

## Brass Fittings

Ctn. Qty.: 10, 2/cd

MILTON PART. NO.	DESC.	THREAD SIZE (NPT)	CARD PACK	ORDER NO.	PRICE PER CARD
S-643	Female	1/4" x 1/4"	2	3350-285	\$3.50
S-646	Male hex nipple	1/4" x 1/4"	2	3350-291	3.58




S-646

## Air Hose Swivel Connector

Attach portable air tools to air hose. 360° swivel in two places prevents hose kinking, and keeps the hose out of the way. Female pipe threads connect to most hose fittings and adapters. Not for use with percussion tools.

MILTON PART. NO.	DESC.	ORDER NO.	PRICE EACH
S-657	1/4" Swivel Connector	3350-320	\$13.96
S-657-1	3/8" Swivel Connector	3350-321	15.32
S-657-2	1/4" Swivel Connector w/Flow Control	3350-322	17.74



S-657-2

## 3-in-1 Air Manifolds

Supply 3 air tools from a single inlet. No need to disconnect and connect for every tool change. Sturdy and lightweight aluminum body.

MILTON PART. NO.	INLET NPT	3 OUTLETS FEMALE NPT	ORDER NO.	PRICE EACH
S-685-4	1/4"	1/4"	3350-354	\$ 14.15
S-685-6	3/8"	1/4"	3350-356	14.65



S-685-4

## Drain Cocks

- Brass body • Steel handle

Ctn. Qty.: 10, 2/cd

MILTON PART. NO.	NPT	CARD PACK	ORDER NO.	PRICE PER CARD
S-614-2	1/8"	2	3350-246	\$ 5.34
S-614-4	1/4"	2	3350-249	5.35



S-614-2

## In-Line Air Flow Regulators

To regulate air pressure to air tools from full flow to complete shut-off. Use as shut-off valve for air and non-corrosive liquids.

- Maximum: 150 PSI
- SCFM 5 @ 100 PSI
- Temperature range: 40° F to 250° F

MILTON PART. NO.	FEMALE NPT	MALE NPT	ORDER NO.	PRICE EACH
S-638	1/4"	1/4"	3350-271	\$20.46
S-638-1	1/4"	1/4" w/gage	3350-272	34.71



S-638-1

## In-Line Lubricator

To lubricate pneumatic tools for full protection by accurately metering correct amount of oil. 1/2 oz capacity.

MILTON PART. NO.	MALE NPT SIZE	FEMALE NPT SIZE	ORDER NO.	PRICE EACH
S-639	1/4"	1/4"	3350-274	\$26.13



S-639

# Signal Bells, Tank Valves, Air Hose



## Tank Valves

Attach portable air tools to air hose. 360° swivel in two places prevents hose kinking, and keeps the hose out of the way. Female pipe threads connect to most hose fittings and adapters. Not for use with percussion tools.

Ctn. Qty.: 10

MILTON PART. NO.	NPT	CARD PACK	ORDER NO.	PRICE PER CARD
S-684	1/8"	2	3350-349	\$4.05
S-684-4	1/4"	2	3350-352	6.31



S-684

## Nylon Re-Koil Air Hose

Assembled with re-usable, full flow male NPT swivel fittings on both ends to avoid twisting and kinking. Individual display bag packaged. Resists abrasions.

- Maximum working pressure: 200 PSI @ 70° F
- Working temperature: -40° F to 180° F (-38° C to 82° C)
- Material: Equivalent to nylon 12
- Color: Yellow



1669

MILTON PART. NO.	HOSE ID	LENGTH	SWIVEL MALE NPT	ORDER NO.	PRICE EACH
1667	1/4"	12'	1/4"	3350-856	\$20.88
1669	1/4"	25'	1/4"	3350-857	26.38
1670	1/4"	50'	1/4"	3350-861	46.79
1674	3/8"	25'	3/8"	3350-872	55.09

## Tank Conversion Kit

Do it yourself kit allows you to convert all no longer allowed R-12 freon tanks to portable air tanks.

WARNING: NOT FOR PROPANE TANK CONVERSION.

Kit contains: filler valve, gage, 4' air hose assembly, manifold, chuck

MILTON PART. NO.	DESC.	ORDER NO.	PRICE EACH
S-682	filler valve, gage, 4' air hose assembly, manifold, chuck	3350-342	\$37.51



S-682

## Swivel End Snubber Hose

Absorb shock to air couplers from impact tools and/or air hammers. Snubber hoses are fitted with a full 360° steel swivel fitting for greater flexibility and easier use.

- Burst pressure: 800 lbs.
- Maximum working pressure: 200 PSI



S-680-1

MILTON PART. NO.	HOSE ID	LENGTH	360° SWIVEL FITTING NPT	BRASS FITTING	ORDER NO.	PRICE EACH
S-680-1	1/4"	5'	Male 1/4"	Female 1/4"	3350-337	\$26.12
S-680-2	3/8"	30"	Male 1/4"	Female 1/4"	3350-338	19.71

## Driveway Signal

Completely self contained unit is easy to install and use just plug into any 110 volt electric outlet. Offers instant signal every time, operating with up to 300 feet of signal hose. For use at service stations, bank or restaurant drive up windows, or any drive up application where an attendant needs to be alerted.

805 DRIVEWAY SIGNAL BELL (6" diameter)  
Order No. 3350-516 Price Each: \$102.66




805

## EPDM 2 Braid Air Hose

Deluxe heavy duty EPDM rubber is designed for tough service station and shop applications. Kink resistant and flexible in extreme temperatures, resists abrasion, weathering and ozone. Assemblies coupled with brass fittings, bulk hose comes without fittings in either a dispensing box or handy reel. Individually boxed. Limited oil resistance.

- Maximum working pressure: 250 PSI
- Burst pressure: 1000 PSI
- Working temperature: -40° F to 190° F (-38° C to 87° C)
- Material: EPDM rubber tube & cover, spiral synthetic yarn reinforcement
- Color: Red



1630

MILTON PART. NO.	HOSE ID	LENGTH	FITTINGS, NPT	ORDER NO.	PRICE EACH
1630	1/4"	25'	Male 1/4" both ends	3350-816	\$44.27
1631	1/4"	50'	Male 1/4" both ends	3350-820	90.78
1632	3/8"	25'	Male 3/8" both ends	3350-821	59.36
1633	3/8"	50'	Male 3/8" both ends	3350-825	109.08

## Remote Control Air Switch & Signal Bell

Deluxe terminal box construction assures maximum sensitivity with long term performance. Weatherproof for use inside and outside. Easy connections with Barrier terminal strip and conduit openings for versatility in installation.

- Conduit type box construction for wall or conduit mounting. Burn out proof coil assures long service.
- 825 REMOTE CONTROL AIR SWITCH  
(use with any voltage from 6V to 220V, 10 amps maximum)  
Order No. 3350-518...Price Each: \$137.02



825

## 800 Series Accessories 819

Ctn. Qty.: 5  
819 HOSE ANCHOR (for 3/8" ID signal hose)  
Order No. 3350-517...Price Each: \$20.20

838 DELUXE DRIVEWAY SIGNAL HOSE SBR RUBBER (3/8" ID 50' length)  
Order No. 3350-521...Price Each: \$64.09

839 DELUXE DRIVEWAY SIGNAL HOSE SBR RUBBER (3/8" ID 300' reel)  
Order No. 3350-522...Price Each: \$333.63



838  
839

Requires Milton air switch #825  
827 REMOTE CONTROLLED SIGNAL BELL (110V)  
Order No. 3350-519...Price Each: \$107.75

- Key slot opening in back makes installation easy. Tone is clear and melodious. Burn out proof coil assures long service.
- Requires Milton Air switch #825



827



## Rotary Tool Kit 4000-2/30



The Dremel 4000 variable speed rotary tool offers the highest performance and most versatility of all Dremel rotary tools. The increased strength of its motor plus electronic feedback circuitry enables consistent performance at all speed levels. Dremel 4000 can use all existing Dremel accessories and attachments plus high-performance attachments to complete the widest range of projects. A slim, ergonomic body provides a 360-degree grip zone for comfort and control in any grip position.

**Kit Contains:**

- Dremel 4000 High Performance Rotary Tool
- Circle Cutter/Straight Edge Guide
- Sanding/Grinding Guide
- Storage Case
- Includes 30 genuine Dremel accessories
- Quick Start Book

**Order No. 3264-030 Price Each: \$118.90**

## Rotary Tool Kit - 4000-6/50



The Dremel 4000 variable speed rotary tool offers the highest performance and most versatility of all Dremel rotary tools. The increased strength of its motor plus electronic feedback circuitry enables consistent performance at all speed levels. Dremel 4000 can use all existing Dremel accessories and attachments plus high-performance attachments to complete the widest range of projects. A slim, ergonomic body provides a 360-degree grip zone for comfort and control in any grip position.

**Kit Contains:**

- Dremel 4000 High Performance Rotary Tool
- Planer attachment • Flex Shaft attachment
- Circle Cutter/Straight Edge Guide
- Sanding/Grinding Guide
- Multipurpose Cutting Guide attachment
- Detail Nose Piece
- Lawn Mower and Garden Tool Sharpening Attachment
- Storage Case • Quick Start Book
- Includes 50 genuine Dremel accessories

**Order No. 3264-034 Price Each: \$200.30**

## Single Speed Rotary Tool Kit 100-N/7

- Ideal for sanding, carving, and drilling.

**Set Includes:**

- 100 Series Single Speed Rotary Tool
- 402 Mandrel
- 407 Coarse 1/2" Sanding Drum • 415 Dressing Stone
- 420 Heavy Duty Emery Cut-Off Wheel
- 432 1/2" 120 Grit Sanding Band
- 932 Aluminum Oxide Grinding Stone
- 84922 Silicon Carbide Grinding Stone
- CORD LENGTH: 6' • SPEED: 35,000 rpm
- VOLTAGE: 120 AC, 50-60 Hz
- WARRANTY: 2 years

**Order No. 3260-098 Price Each: \$ 58.10**



## Variable Speed Rotary Tool Kit 3000-1/24

- Rotary Tool
- Includes Storage Case and 24 Accessories
- Sanding/Grinding Guide Attachment
- EZ Twist™ nose cap with wrench for fast accessory changes
- Tool works with all Dremel accessories and attachments, except PL400 and MS400
- Variable speed from 5,000 to 32,000 RPM

- Cool-running ball bearing construction for smooth and quiet operation
- Replaceable motor brushes extend tool life
- Four year warranty

**Order No. 3263-001 Price Each: \$ 96.90**



## Electric Engraver - Model 290-02



**Contains:**

- Engraver Tool • Carbide Point (9924) • Letter/Number Template
- Engraves permanently on metal, wood, plastic, ceramics and more.
- Protect valuables, discourage theft.
- Perfect for hobbies and crafts.

**Order No. 3260-290 Price Each: \$ 22.75**

Extra CARBIDE Point for normal applications:  
**Order No. 3269-924 Price Ea.: \$6.10**

Extra DIAMOND Point for Commercial Work:  
**Order No. 3269-929 Price Ea.: \$ 17.47**

## Right Angle Attachment Model 575



- Enhances the versatility of the Dremel tool, by allowing use in hard-to reach areas
- Ball bearings and spiral bevel gears provide smooth and cool operation
- Coupling system allows orientation of attachment in 12 different directions
- Quick connect system easily attaches to rotary tool in place of the housing cap, no wrench required
- Compact, durable design, for hard-to reach places

**Order No. 3260-575 Price Each: \$ 24.30**

## Grinding/Sharpening

### Silicon Carbide Grinding Stones




Order No. 3263-142 Price Ea. \$ 2.82  
 Order No. 3264-922 Price Ea. \$ 5.07  
 Order No. 3265-422 Price Ea. \$ 2.82  
 Order No. 3269-952 Price Ea. \$ 2.82

### Aluminum Oxide Grinding Stones




Order No. 3260-932 Price Ea. \$ 2.83  
 Order No. 3260-953 Price Ea. \$ 4.33  
 Order No. 3260-952 Price Ea. \$ 2.83  
 Order No. 3268-215 Price Ea. \$ 2.82

### Cut-Off Wheels




Order No. 3260-409 Price/Pk. \$ 6.38  
 Order No. 3260-420 Price/Pk. \$ 6.65  
 Order No. 3260-426 Price/Pk. \$ 8.52

## Carving/Engraving



Order No. 3260-115 Price/Pk. \$ 7.57  
 Order No. 3260-117 Price/Pk. \$ 7.58  
 Order No. 3260-121 Price Ea. \$ 5.27  
 Order No. 3260-125 Price/Pk. \$ 7.57  
 Order No. 3260-192 Price/Pk. \$ 7.22  
 Order No. 3260-194 Price/Pk. \$ 7.93  
 Order No. 3260-199 Price Ea. \$ 6.08  
 Order No. 3260-107 Price/Pk. \$ 3.92

## Structured Tooth Tungsten Carbide Cutters



Order No. 3269-931 Price Ea. \$ 12.75  
 Order No. 3269-933 Price Ea. \$ 12.75  
 Order No. 3269-935 Price Ea. \$ 12.75

## Cleaning/Polishing



Order No. 3260-414 Price Ea. \$ 2.45  
 Order No. 3260-422 Price Ea. \$ 2.45  
 Order No. 3260-429 Price Ea. \$ 2.45

## Bristle Brushes




Order No. 3262-403 Price/Pk. \$ 5.08  
 Order No. 3262-404 Price/Pk. \$ 4.82

## C.S. Wire Brushes



Order No. 3262-428 Price/Pk. \$ 5.08  
 Order No. 3262-442 Price/Pk. \$ 4.82  
 Order No. 3262-443 Price/Pk. \$ 5.60

## Tungsten Carbide Cutters



Order No. 3269-901 Price Ea. \$ 9.48  
 Order No. 3269-903 Price Ea. \$ 9.48  
 Order No. 3269-909 Price Ea. \$ 9.50

## Sanding




Order No. 3260-430 Price Ea. \$ 4.85  
 Order No. 3260-407 Price Ea. \$ 3.97  
 Order No. 3260-408 Price/Pk. \$ 2.85  
 Order No. 3260-432 Price/Pk. \$ 2.83  
 Order No. 3260-413 Price/Pk. \$ 3.10

## Flapwheels



Order No. 3260-502 Price Ea. \$ 6.38  
 Order No. 3260-505 Price Ea. \$ 6.38

## Collets & Chucks



Order No. 3264-486 Price Ea. \$ 10.10  
 Order No. 3260-480 Price Ea. \$ 2.82  
 Order No. 3260-483 Price Ea. \$ 2.83

## EZ Lock™ Mandrels/Wheels



Order No. 3261-402 Price Ea. \$ 9.70  
 Order No. 3261-423 Price Ea. \$ 4.18  
 Order No. 3261-545 Price Ea. \$ 25.42  
 Order No. 3261-409 Price/Pk. \$ 11.40  
 Order No. 3261-456 Price/Pk. \$ 11.75  
 Order No. 3261-511 Price/Pk. \$ 4.35  
 Order No. 3261-471 Price Ea. \$ 7.98  
 Order No. 3261-472 Price Ea. \$ 8.00  
 Order No. 3261-473 Price Ea. \$ 8.00

## Mandrels



Order No. 3260-401 Price Ea. \$ 3.23  
 Order No. 3260-402 Price Ea. \$ 2.43

## 709-02 110 Pcs. Super Accessory Kit

This versatile and re-usable accessory kit includes everything you need to cut, grind, sand, polish, drill, sharpen, clean and more.

Order No. 3260-709  
 Price Each: \$ 29.12



## 710-08 160-Pcs. All Purpose Accessory Kit

This versatile and re-usable accessory kit includes everything you need to cut, grind, sand, polish, drill, sharpen, clean and more. Includes 8 EZ Lock™ accessories.

Order No. 3260-710  
 Price Each: \$ 40.67

